



**Part Number: 8205**

Electronic, 2 C #20 Str TC, PVC Ins, PVC Jkt, CMG

[Request Sample](#)

## Product Description

Electronic, 2 Conductor 20AWG (7x28) Tinned Copper, PVC Insulation, PVC Outer Jacket, CMG

## Technical Specifications

### Physical Characteristics (Overall)

#### Conductor

AWG	Stranding	Material	No. of Pairs
20	7x28	TC - Tinned Copper	1

Conductor Count:	2
Total Number of Pairs:	1
Conductor Size:	20 AWG

#### Insulation

Material	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.0145 in

#### Color Chart

Number	Color
1	Black & Red

#### Outer Shield Material

Material
Unshielded

#### Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.18 in	0.025 in

### Electrical Characteristics

#### Conductor DCR

Nominal Conductor DCR
10 Ohm/1000ft

#### Capacitance

Nom. Capacitance Conductor to Conductor
24.5 pF/ft

#### Current

Max. Recommended Current [A]
3.7 Amps per conductor @ 20°C

#### Voltage

UL Voltage Rating
300 V RMS

## Temperature Range

Operating Temp Range:	-20°C To +60°C
-----------------------	----------------

## Mechanical Characteristics

Bulk Cable Weight:	16 lbs/1000ft
Max Recommended Pulling Tension:	28 lbs
Min Bend Radius/Minor Axis:	2 in

## Standards

NEC Articles:	800
NEC/(UL) Specification:	CMG
CEC/C(UL) Specification:	CMG
CPR Euroclass:	Eca

## Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

## Flammability, LSOH, Toxicity Testing

UL Flammability:	UL1685 FT4 Loading
CSA Flammability:	FT4
UL voltage rating:	300 V RMS

## Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

## Part Number

### Variants

Item #	Color	Footnote
8205.00U152	Chrome	
8205.00U305	Chrome	
8205.01152	Chrome	
8205.01305	Chrome	
8205 0601000	Chrome	C
8205 0605000	Chrome	
8205 060U500	Chrome	

Footnote:	C - CRATE REEL PUT-UP.
-----------	------------------------

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.