8814 CharGuard™





RECOMMENDED FOR THESE RISKS: Heat & cold Abrasion Slips RECOMMENDED FOR THESE LINES OF WORK: Metallurgical industry Food industry

Non woven liner Neoprene spray

DESCRIPTION

- · Fully coated
- · Slip-on designed gauntlet
- Textured finish
- Without special treatment
- Cut and sewn
- Approved for food handling
- · Heat protection up to 260°C

BENEFITS

- A comfortable, supple glove providing effective protection against abrasion and with a very good grip
- · Protects the hand against hot temperatures
- · Impermeable for working in damp or greasy environments
- · Easy to put on and remove
- · Surface provides better grip
- · Lower allergy risks
- · Wrist well protected
- Low-soil colour

AVAILABLE SIZES	7/S • 8/M • 9/L • 10/XL
WELTING COLOUR CORRESPONDS TO SIZE White 7/S • Blue 8/M • Red 9/L • Black 10/XL	
LENGTH Dependent on size, in mm (flat)	355
PACKAGING Pairs or pieces per pack/box	12/72
COLOUR OF SUPPORT/COATING	Black

RECOMMENDATIONS FOR USE

- · Store away from light and humidity
- Cleaning: The gloves can be laundered between 40 60°C max. However, the customer or launderer is responsible for the performance of the gloves after laundering. Best cannot be held liable for this.
- Do not wear gloves when there is a risk of entanglement by moving parts of machines.
- · Gloves must not come in contact with an open flame.
- Potential allergens: carbamate

EN 407 - 2004

X2XXXX

ABRASION CUTTING 0 1 2 <u>3</u> 4 0 1 <u>2</u> 3 4 5

TEARING PUNCTURE

012<u>3</u>4

0 1 <u>2</u> 3 4

EN388 - 2003



Globus Building 38 Wheel Forge Way Trafford Park, Manchester M17 1EH Tel: 0161 877 4747 Fax: 0161 87

Tel: 0161 877 4747 Fax: 0161 877 4746 www.globus.co.uk

EC compliance certificate delivered by the notified body 0321 SATRA House - Rockingham Road, Kettering - Northampshire NN16 9JH - United Kingdom

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

 FLAMMABILITY
 CONTACT HEAT

 X 1 2 3 4
 0 1 2 3 4

 CONVECTIVE HEAT
 RADIANT HEAT

 X 1 2 3 4
 X 1 2 3 4

 SMALL SPLASHES OF MOLTEN METAL
 LARGE SPLASHES OF MOLTEN METAL

 X 1 2 3 4
 X 1 2 3 4

[Updated 01/02/2010]

