

Eaton 171336

Catalog Number: 171336

Eaton Moeller® series SL4 Ba15d continuous light module, orange



General specifications

Product Name	Catalog Number
Eaton Moeller® series SL4 Continuous light module	171336
	EAN
	4015081678730
Product Length/Depth	Product Height
43 mm	75 mm
Product Width	Product Weight
43 mm	0.037 kg
Certifications	Catalog Notes
Certified by UL for use in Canada	Without light elements
UL Category Control No.: NKCR	
UL 508	
IEC/EN 60529	
UL report applies to both US and Canada	
CSA Class No.: NKCR7	
CE	
CSA-C22.2 No. 14-10	
CSA-C22.2 No. 94-91	
UL	
UL File No.: E29184	
IEC/EN 60947-5-1	

Features & Functions

Color

Orange

Enclosure color

Black

Functions

Continuous light

Light modules

Filament lamp max. 4 W

Number of modules

Max. 10 (with base for mounting on both sides)

Max. 5 (with standard base)

General

Connection to SmartWire-DT

No

Degree of protection

NEMA 4X

IP66

Lifespan, electrical

3,000 h

Light type

Continuous light

Material

Cap: Polycarbonate (PC)

Enclosure: Polycarbonate (PC)

Mounting Method

BA15d lamp socket

Mounting position

As required

Overvoltage category

III

Pollution degree

3

Product Category

SL signal towers

Radiation angle

360 °

Rated impulse withstand voltage (Uimp)

4000 V AC

Shock resistance

Mechanical, According to IEC/EN 60068-2-27

15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Type

Continuous light module

Voltage type

AC/DC

Climatic environmental conditions

Ambient operating temperature - min

-30 °C

Ambient operating temperature - max

60 °C

Climatic proofing

Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78

Electrical rating

Leakage current

0.003 A

Power consumption

Max. 4 W with the specified voltages

Rated insulation voltage (Ui)

250 V

Rated operational voltage (Ue) at AC - min

24 V

Rated operational voltage (Ue) at AC - max

250 V

Rated operational voltage (Ue) at DC - min

24 V

Rated operational voltage (Ue) at DC - max

250 V

Resources

Brochures

[SL4, SL7, SLC Stack light overview brochure BR047017](#)

Catalogs

[eaton-rmq-titan-brochure-br047004en-en-us.pdf](#)

[eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf](#)

Declarations of conformity

[DA-DC-00004253.pdf](#)

[DA-DC-00004257.pdf](#)

Drawings

[eaton-operating-sl4-continuous-light-dimensions.eps](#)

[eaton-operating-button-sl7-continuous-light-symbol.eps](#)

[eaton-operating-sl7-continuous-light-symbol.eps](#)

eCAD model

[ETN.171336.edz](#)

Installation instructions

[IL047005ZU](#)

Installation videos

[Signal towers SL4 and SL7](#)

mCAD model
DA-CS-sl4_bfl4
DA-CD-sl4_bfl4



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia