1376477-6 ACTIVE

AMP Signal Double Lock

TE Internal #: 1376477-6

Housing, Plug, Wire-to-Board, 6 Position, 2.5 mm [.098 in] Centerline, Crimp, 1 Row, Natural, Printed Circuit Board, AMP

Signal Double Lock

View on TE.com >



Connectors > PCB Connectors > Wire-to-Board Connectors > Wire-to-Board Connector Assemblies & Housings











Connector Product Type: Housing
Connector & Housing Type: Plug
Connector System: Wire-to-Board

Number of Positions: 6

Centerline (Pitch): 2.5 mm [.098 in]

Features

Product Type Features

Connector Product Type	Housing
Connector & Housing Type	Plug
Connector System	Wire-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Positions	6
Number of Rows	1
Electrical Characteristics	
Operating Voltage	50 VDC
Body Features	
Primary Product Color	Natural

Contact Features



Contact Layout Contact Base Material Phosphor Bronze Contact Type Pin Contact Current Rating (Max) 2.5 A Termination Features Termination Method to Wire & Cable Crimp Mechanical Attachment Strain Relief Without Panel Mount Feature Without Mating Retention Type Latch PCB Mount Retention Without Mating Retention Without Mating Retention Connector Mounting Type Cable Mount (Free-Hanging) Housing Features Housing Material Centerline (Pitch) Dimensions
Contact Type Contact Current Rating (Max) Termination Features Termination Method to Wire & Cable Mechanical Attachment Strain Relief Without Panel Mount Feature Without Mating Retention Type Latch PCB Mount Retention Without Mating Retention Without Mating Retention Connector Mounting Type Housing Features Housing Material Nylon 66 GF Centerline (Pitch)
Contact Current Rating (Max) Termination Features Termination Method to Wire & Cable Crimp Mechanical Attachment Strain Relief Without Panel Mount Feature Without Mating Retention Type Latch PCB Mount Retention Without Mating Retention Without Mating Retention Connector Mounting Type Cable Mount (Free-Hanging) Housing Features Housing Material Nylon 66 GF Centerline (Pitch) 2.5 mm[.098 in]
Termination Features Termination Method to Wire & Cable Crimp Mechanical Attachment Strain Relief Without Panel Mount Feature Without Mating Retention Type Latch PCB Mount Retention Without Mating Retention Without Mating Retention Connector Mounting Type Cable Mount (Free-Hanging) Housing Features Housing Material Nylon 66 GF Centerline (Pitch) 2.5 mm[.098 in]
Termination Method to Wire & Cable Mechanical Attachment Strain Relief Without Panel Mount Feature Without Mating Retention Type Latch PCB Mount Retention Without Mating Retention Without Mating Retention Connector Mounting Type Cable Mount (Free-Hanging) Housing Features Housing Material Nylon 66 GF Centerline (Pitch) Crimp Crimp
Mechanical Attachment Strain Relief Without Panel Mount Feature Without Mating Retention Type Latch PCB Mount Retention Without Mating Retention Without Mating Retention Connector Mounting Type Cable Mount (Free-Hanging) Housing Features Housing Material Nylon 66 GF Centerline (Pitch) 2.5 mm[.098 in]
Strain Relief Without Panel Mount Feature Without Mating Retention Type Latch PCB Mount Retention Without Mating Retention With Connector Mounting Type Cable Mount (Free-Hanging) Housing Features Housing Material Nylon 66 GF Centerline (Pitch) 2.5 mm[.098 in]
Panel Mount Feature Mating Retention Type Latch PCB Mount Retention Without Mating Retention With Connector Mounting Type Cable Mount (Free-Hanging) Housing Features Housing Material Nylon 66 GF Centerline (Pitch) 2.5 mm[.098 in]
Mating Retention Type PCB Mount Retention Without Mating Retention With Connector Mounting Type Cable Mount (Free-Hanging) Housing Features Housing Material Nylon 66 GF Centerline (Pitch) 2.5 mm[.098 in]
PCB Mount Retention Without Mating Retention With Connector Mounting Type Cable Mount (Free-Hanging) Housing Features Housing Material Nylon 66 GF Centerline (Pitch) 2.5 mm[.098 in]
Mating Retention Connector Mounting Type Cable Mount (Free-Hanging) Housing Features Housing Material Nylon 66 GF Centerline (Pitch) 2.5 mm[.098 in]
Connector Mounting Type Cable Mount (Free-Hanging) Housing Features Nylon 66 GF Centerline (Pitch) 2.5 mm[.098 in]
Housing Features Housing Material Nylon 66 GF Centerline (Pitch) 2.5 mm[.098 in]
Housing Material Centerline (Pitch) Nylon 66 GF 2.5 mm[.098 in]
Centerline (Pitch) 2.5 mm[.098 in]
Dimensions
Connector Height 6.5 mm[.256 in]
Wire Size 26 – 22 AWG
Connector Length 17.5 mm[.688 in]
Usage Conditions
Operating Temperature Range -40 – 105 °C[-40 – 221 °F]
Operation/Application
Circuit Application Power & Signal
Packaging Features
Packaging Method Bag & Box
Packaging Quantity 300

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant



China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts











Also in the Series | AMP Signal Double Lock





Connector Caps & Covers(1)



Connector Contacts(14)




Connector Hardware(19)



Connector Seals & Cavity Plugs(10)



Insertion & Extraction Tools(1)



PCB Headers & Receptacles(146)




Rectangular Power Connectors(46)



Wire-to-Board Headers & Receptacles (146)


Customers Also Bought




TE Part #172520-2 2P 2.5MM MINI AMP-IN HDR HSG



TE Part #42563-2 250 FASTON FLAG REC 12-10 AWG TPBR



TE Part #180923 FF 250 REC HSG 2P NYLON NAT



TE Part #1871859-1 GIC 2.5 REC CONT TIN PLATE TYPE (MTYPE)



TE Part #177914-2

AMP POWER DBL LOCK REC (S)



TE Part #4-1971030-5
5POS PLUG HOUSING FOR GIC 2.0
EV SERIES



TE Part #1747066-2 GRACE INERTIA CONN 2.5 PLUG HSG 2P NATUR



TE Part #1376476-1
2.5 SIGNAL MATE REC CONTACT



TE Part #179938-1
AMP POWER DBL LOCK PLUG HSG 3P



TE Part #42563-8 250 FASTON FLAG REC 12-10 AWG TPBZ

Documents



Product Drawings

2.5MM PITCH SIGNAL MATE CONN

English

CAD Files

Customer View Model

ENG_CVM_CVM_1376477-6_E.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1376477-6_E.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1376477-6_E.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English