

## NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIAL:


HOUSING: THERMOPLASTIC SEAL: SILICONE RUBBER

- 2. MODIFICATIONS: REDUCED DIAMETER WIRE SEAL
- 3. SPECIFICATIONS:
  - 3.1 CURRENT RATING: 13 AMPS
  - 3.2 OPERATING TEMPERATURE: -55°C TO +125°C
  - 3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC. 3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.

  - 3.5 MOISTURE RESISTANCE: IP67 ( MATED CONDITION )
  - 3.6 MATING CYCLE DURABILITY: 100 CYCLES
  - 3.7 RoHS COMPLIANT
- 4. MATING PART: AT06-3S\* RECEPTACLE ( \* = MODIFICATIONS AND COLORS )
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.



CONTACT	MIN. INSUL	MAX. INSUL	TYPICAL
SIZE	O.D.	O.D.	WIRE RANGE
16	1.35 mm (.053 ln)	3.05 mm (.120 ln)	14 - 20 AWG



PART NUMBER CHART				
COLOR	PART NUMBER			
GREY	AT04-3P-RD01			
BLACK	AT04-3P-RD01BLK			
BLUE	AT04-3P-RD01BLU			
BROWN	AT04-3P-RD01BRN			
GREEN	AT04-3P-RD01GRN			
RED	AT04-3P-RD01RED			
WHITE	AT04-3P-RD01WHT			
YELLOW	AT04-3P-RD01YEL			

	SEE PART N	UMBER CHART							
	PART NUMBER			DESCRIPTION			ITEM		
QUANTITY	TITY MATERIALS LIST								
UNLESS OTHERWISE SPECIFIED  1) All dimensions are in metric(mm).  2) Tolerances are as follows:  1 PL DEC ±0.30  2 PL DEC ±0.15  3 PL DEC ±0.08  4 Angles ±1°		SIGNATURI	S DA	\TE	Amphono		mphonol		
		DRAWN: JARRY	04J	AN14	Ampheno		unbuenoi		
		CHECKED:			Sine Systems - www.amphenol-sine.com		_		
3) Note reference	= <u>x</u>	ENGINEER:			44724 Morley DrIve Clinton Township, MI 48036				
MATERIAL SPECIFICA	TIONS:	APPROVAL:						-	
THIS D PROCESS SPECIFICATIONS: SPECIFICATIONS: SPECIFICATIONS SPECIFICATIONS OF RES		CUSTOMER:		RECEPTACLE, 3 PIN, AT SERIES,					
		THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY, DESIGN FEATURES.		REDUCED DIAMETER WIRE SEAL					
		SPECIFICATIONS AND PE SHOWN HEREON ARE TH THE AMPHENOL CORPOR OF REPRODUCTION ARE			B	C-	AT04-3P-RD01XXX	A3	
NEXT ASSY:			SCALE: N	IONE	SHEET 1 OF	1			