

## DIN rail, unperforated - NS 15 UNPERF 2000MM - 1401695

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




DIN rail, unperforated, Standard profile, width: 15 mm, height: 5 mm, acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, length: 2000 mm, color: silver

### Your advantages

- All DIN rails are also available cut to length
- Particular attention has been paid to high dimensional accuracy and surface tempering
- The design of the DIN rails corresponds to European standard EN 60715

### Key Commercial Data

Packing unit	5 pc
Minimum order quantity	5 pc
GTIN	 4 017918 020507
GTIN	4017918020507
Weight per Piece (excluding packing)	330.000 g
Custom tariff number	72166190
Country of origin	Germany

### Technical data

#### Dimensions

Height	5 mm
Length	2000 mm
Width	15 mm
Hole width	0.00 mm
Hole height	0.00 mm
Drill hole spacing	0.00 mm

#### General

Material	Steel
Coating	galvanized, passivated with a thick layer

# DIN rail, unperforated - NS 15 UNPERF 2000MM - 1401695

## Technical data

### General


Color	silver
-------	--------

### Standards and Regulations

Test standard	acc. to EN 60715
Connection in acc. with standard	IEC / EN

## Drawings

Dimensional drawing



## Classifications

### eCl@ss

eCl@ss 4.0	27110804
eCl@ss 4.1	27110804
eCl@ss 5.0	27141143
eCl@ss 5.1	27141100
eCl@ss 6.0	27400600
eCl@ss 7.0	27400602
eCl@ss 8.0	27400602
eCl@ss 9.0	27400602

### ETIM

ETIM 2.0	EC001285
ETIM 3.0	EC001285
ETIM 4.0	EC000212
ETIM 5.0	EC000212
ETIM 6.0	EC001285
ETIM 7.0	EC001285

### UNSPSC

UNSPSC 6.01	30212109
UNSPSC 7.0901	39121708

## DIN rail, unperforated - NS 15 UNPERF 2000MM - 1401695

### Classifications

#### UNSPSC

UNSPSC 11	39121708
UNSPSC 12.01	39121708
UNSPSC 13.2	39121708