

General Information

Extended Product Type:	S802PV-M125
Product ID:	2CCP812001R1849
EAN:	7612271211240
Catalog Description:	High Performance Circuit Breaker - S800PV-M - Disconnecter - Number of poles 2 - Rated operational current 125A - Rated operational voltage 800V DC
Long Description:	S802PV-M125 2 Pole DC main switch 125A 1.5kA 800VDC DC main switch

Categories

Products » Low Voltage Products and Systems » Modular DIN Rail Products » High Performance Circuit Breakers HPCBs

Ordering

EAN:	7612271211240
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362020

Dimensions

Product Net Width:	54 mm
Product Net Depth:	82.5 mm
Product Net Height:	95 mm
Product Net Weight:	0.43 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	105 mm
Package Level 1 Length:	60 mm
Package Level 1 Height:	99 mm
Package Level 1 Gross Weight:	0.45 kg
Package Level 1 EAN:	7612271211240

Environmental

Ambient Air Temperature:	Operation -25 ... +60 °C Storage -40 ... +70 °C
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Technical

Standards:	IEC 60947-3
Number of Poles:	2
Rated Current (I_n):	125
Rated Operational Voltage:	800 V DC
Power Loss:	7.8 W
Contact Position Indication:	ON / OFF / TRIP
Connecting Capacity:	Flexible 1 ... 50 mm ² Flexible Stranded 1 ... 70 mm ²

Certificates and Declarations (Document Number)

Declaration of Conformity - CE:	2CCC413036D0601
RoHS Information:	2CCC413008D0201

Classifications

ETIM 4.0:	EC000216 - Switch disconnecter
ETIM 5.0:	EC000216 - Switch disconnecter
Object Classification Code:	F



