

KEMET Part Number: ALC10A471EH500
(A521HK471M500A)

ALC10, Aluminum Electrolytic, 470 uF, 20%, 500 VDC, -40/+85°C



General Information	
Supplier:	KEMET
Series:	ALC10
Dielectric:	Aluminum Electrolytic
Description:	Snap-In, Aluminum Electrolytic
RoHS:	Yes
Lead:	2 Pin
AEC-Q200:	No
Notes:	Dimensions D And L Include Slewing
Shelf Life:	156 Weeks

Dimensions	
D	40mm +1mm
L	60mm +/-2mm
S	10mm +/-0.1mm
LL	6.3mm +/-1mm
F	2mm +/-0.1mm

Specifications	
Capacitance:	470 uF
Capacitance Tolerance:	20%
Voltage DC:	500 VDC, 550 VDC (Surge)
Temperature Range:	-40/+85°C
Rated Temperature:	85°C
Life:	18000 Hrs (Rated Voltage And Ripple Current At 85C), 29000 Hrs (Rated Voltage at 85C)
Resistance:	285 mOhms (100Hz 20C), 201 mOhms (10kHz 20C)
Ripple Current:	3.56 Amps (100Hz 85C), 6.43 Amps (10kHz 85C)
Leakage Current:	1410 uA (5min 20°C)

Packaging Specifications	
Weight:	98 g
Slewing:	Yes
Packaging:	Bulk, Bag