

Technical specs

VECUT41 - VENICUT41

Name:

TAEKI® S KNITTED GLOVE - NITRILE-COATING PALM

Size:

07 - 08 - 09 - 10

Colour:

Grey



Description :

Seamless knitted glove. TAEKI® S high performance polyethylene fibre. Nitrile coating on palm and fingertips. 10-cm elasticated wrist. Gauge 13.

Materials:

Synthetic fibre TAEKI® S (high performance)
Coated : 100% nitril.

Instructions for use:

Gloves for general use in cutting atmosphere, with no chemical, microbiological, electrical or thermal hazards.

Limits to use:

Do not use other than for the purpose defined in the instructions for use below. *Users are reminded that gloves with very high resistance to traction (level 4) should not be used when there is a risk of grabbing by moving machines. These gloves do not contain any substances known to be carcinogenic or toxic. Contact with the skin may cause allergic reactions in sensitive persons (natural latex, in the cuff wrists of some gloves). In the event of a reaction, cease use and consult a doctor. Before using these gloves, check that they are intact. Replace if necessary.

Instructions for storage:

Store in a cool, dry place away from frost and light in their original packaging.

Instructions for cleaning / maintenance:

No special maintenance is recommended for these types of gloves.

Performances :

The levels are obtained on the palm of the glove. They are in increasing levels of performance (from 0 to 4 or 5). 0 indicates that the glove has a lower performance level than the minimum for the individual hazard given. X: indicates that the glove has not been subjected to testing or the test method is not suitable due to the design of the gloves or the material.

- Abrasion (from 0 to 4): Ability of the glove to withstand wear
- Cutting (from 0 to 5): Ability of the glove to withstand cutting
- Tearing (from 0 to 4): Ability of the glove to withstand tearing*
- Puncture (from 0 to 4): Ability of the glove to withstand puncture
- Dexterity (from 0 to 5): Manual ability to accomplish a task

The higher the performance, the greater the ability of the glove to withstand the associated risk. Performance levels are based on the results of laboratory tests, which do not necessarily reflect real conditions in the workplace.

This glove complies with the European directive 89/686, notably regarding ergonomics, innocuousness, comfort, ventilation and flexibility, with EN420:2003 (dexterity 5) and EN388:2003(4,4,4,4) European standards.

Technical specs

VE CUT41 - VENICUT41

- **EN388:2003** Protective gloves against mechanical Risks (Levels obtained on the palm)



4 : Resistance to abrasion (from 0 to 4)

4 : Resistance to cut (from 0 to 5)

4 : Resistance to tear (from 0 to 4)

4 : Resistance to perforation (from 0 to 4)