

XENON S1P



Standard EN ISO 20345 : 2011



LEMAITRE

Safety since 1974



ParaBolic®
Technology

- Excellent grip
- Anti-fatigue spring effect
- MSD prevention

Size 35 to 48

Réf. XENOS1PGR

Product Highlights



- **Abrasion resistant 3D textile upper and suede finish leather upper:** very good ventilation inside the shoe, quick drying.

- **Highly breathable 3D textile lining** thanks to its honeycomb structure, pleasant feeling of comfort.

- **Interlocking heel:** reinforced stability, foot support



- **Protective Toe-Cap :** stainless steel



- **Puncture-resistant midsole:** stainless steel



SPORTY PU2D antistatic sole

- **Injection below foot level:** adaptation of the leather to the shape of the foot, great flexibility of the sole and excellent breathability
- **Optimized grip surface and rounded heel strike:** unisex flat sole with a «sports» look
- **Parabolic® Patent :** anti-fatigue spring effect, reinforced stability
- **Rounded heel strike:** respects the natural rolling of the foot, comfort when driving

USAGE

- Construction workers, logisticians and drivers



lemaitre-securite.com

An exacting attitude to quality is our culture, safety our priority



XENON S1P



Standard EN ISO 20345 : 2011

Characteristics of the upper

- **Upper material:** abrasion-resistant 3D textile and split leather velour finish
- **Tongue with gusset:** 3D abrasion resistant textile
- **Lining:** micro-ventilated 3D textile

Characteristics of the sole

- **Designation:** SPORTY
- **Material:** polyurethane / polyurethane
- **Antistatic sole**
- **SRA Adhesion coefficient:**
forward flat slip: 0,37 (standard $\geq 0,32$)
forward heel slip: 0,32 (standard $\geq 0,28$)
- **SRB Adhesion coefficient:**
forward flat slip: 0,27 (standard $\geq 0,18$)
forward heel slip: 0,20 (standard $\geq 0,13$)

VARIANT



Xenon S1 SRC
XENOS10GR

Practical information

Weight of one shoe size 42: 705 g

CERTIFICATION N° 0075/007/161/05/19/1693 EXT 47/04/20

Packaging

size 35 to 43

shoebox 315 x 220 x 125 mm

carton 635 x 445 x 325 mm

10 shoeboxes per carton

size 44 to 48

shoebox 355 x 220 x 130 mm

carton 660 x 450 x 360 mm

10 shoeboxes per carton

Gencods

35	3237154378359	42	3237154378427
36	3237154378366	43	3237154378434
37	3237154378373	44	3237154378441
38	3237154378380	45	3237154378458
39	3237154378397	46	3237154378465
40	3237154378403	47	3237154378472
41	3237154378410	48	3237154378489

Memo for basic and additional requirements of the standard EN ISO 20345: 2011

Safety Footwear

SBP



S1



(A) (E) (Fo)

S1P



(A) (E) (Fo)

S2



(A) (E) (Fo) (Wru)

S3



(A) (E) (Fo) (Wru)



200 J toe-cap: protection of the forefoot against impact and crushing.



Anti-perforation insert 1100 N: foot protection against perforation.



Anti-static footwear



Shock absorption at the heel



Fuel oil-resistant outsole



Water penetration and water absorption resistant upper



Electrostatic discharge



Insulation against cold



Insulation against heat



Outsole resistance to hot contact



Water resistant



Ankle protection



Slip-resistance on ceramic floors with detergent



Slip-resistance on steel floors with glycerol



= (SRA) + (SRB)

Lemaitre Sécurité

17 rue de Bitschhoffen - CS 90024
F - 67350 Val de Moder
Tél. +33 (0)3 88 72 28 80



LEMAITRE
Safety since 1974

Member of
SINAMAP



DON_LS 04 TDS 0070
update: 06/07/21