

## Panasonic Air to Water (Aquarea H/J) to Modbus RTU Interface

Item number: INMBSPAN001A000

The Panasonic-Modbus interface allows full bidirectional communication between Panasonic Air to Water (Aquarea H/J) units and Modbus RTU (RS-485) networks. The interface acts as a server device for the installation, accessing all signals from the Air to Water unit.



*Panasonic Air to Water to Modbus RTU - 1 AW unit*

### Features and benefits

- ✓ **Modbus RTU (EIA-485) server device**  
The interface acts as a Modbus server device through its Modbus RTU (EIA-485 connector) port.
- ✓ **Energy savings through a window contact function**  
This function helps minimize costs, as HVAC systems are a major building energy consumer.
- ✓ **AC unit control by both the remote and Modbus RTU**  
The AC unit can be simultaneously controlled by the manufacturer's remote controller and Modbus RTU.
- ✓ **Multiple mounting options**  
Mounting options include DIN rail, wall, or, in some AC models, even inside the indoor unit.
- ✓ **Dual configuration options**  
Configuration is carried out through the interface's onboard DIP switches and the Modbus interface.
- ✓ **Total unit control and monitoring from Modbus RTU**  
Through internal variables, running hours counter (for maintenance purposes), and error indication.
- ✓ **No external power required**  
The interface is powered directly from the AC unit, so no external power supply is required.

# Panasonic Air to Water (Aquarea H/J) to Modbus RTU Interface



General	
Net Width (mm)	53
Net Height (mm)	93
Net Depth (mm)	58
Net Weight (g)	160
Packed Width (mm)	140
Packed Height (mm)	85
Packed Depth (mm)	108
Packed Weight (g)	200
Operating Temperature °C Min	0
Operating Temperature °C Max	70
Storage Temperature °C Min	-20
Storage Temperature °C Max	85
Power Consumption (W)	1.2
Input Voltage (V)	From the AC unit.
Power Connector	Other
Configuration	DIP Switch
Capacity	1 Air-to-Water unit.
Installation Conditions	This gateway is designed to be mounted inside an enclosure. If the unit is mounted outside an enclosure, precautions should always be taken to prevent electrostatic discharge to the unit. When working inside an enclosure (e.g., making adjustments, setting switches, etc.), typical anti-static precautions should always be followed before touching the unit.
Content of Delivery	Intesis gateway and installation manual.

# Panasonic Air to Water (Aquarea H/J) to Modbus RTU Interface



## General

Mounting	DIN rail mount (bracket included), Wall mount
Housing Materials	Plastic
Warranty (years)	3 years
Packaging Material	Cardboard

## Identification and Status

Product ID	INMBSPAN001A000
Country of Origin	Spain
HS Code	8517620000
Export Control Classification Number (ECCN)	EAR99

## Physical Features

Connectors / Input / Output	EIA-485, AC port.
LED Indicators	1 x Operational status
DIP & Rotary Switches	4x DIP Switch

## Certifications and Standards

ETIM Classification	EC001604
WEEE Category	IT and telecommunications equipment

