

# Eaton 266666

Catalog Number: 266666

Eaton Moeller series NZM - Molded Case Circuit Breaker. Main switch assembly kit, right, frame size 2, M

General specifications



Product Name	Catalog Number
Eaton Moeller series NZM operating element	266666
	EAN
	4015082666668
Product Length/Depth	Product Height
190 mm	220 mm
Product Width	Product Weight
190 mm	2.016 kg
Compliances	Certifications
IEC	UL489
UL/CSA	UL (File No. E140305)
RoHS conform	CSA certified
	CSA (File No. 22086)
	UL (Category Control Number DIHS)
	CSA (Class No. 1437-01)
	CSA-C22.2 No. 5-09
	CE marking
	IEC60947
	UL listed

## Product specifications

### Used with

N(S)2(-4)

NZM2(-4)

PN2(-4)

### Type

Accessory Main switch assembly kit for side panel mounting

### Special features

External warning plate/designation label can be clipped on. For enhanced busbar tag shroud on the incomer side, please order IP2X protection against contact with a finger. Kit for use as a main switch

### Features

Standard: black / gray

Lockable

For direct mounting of circuit-breaker and handle in the side wall of the control cabinet

#### 10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

#### 10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

#### 10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

#### 10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

#### 10.2.2 Corrosion resistance

Meets the product standard's requirements.

##### 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

##### 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

##### 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

## Resources

### Brochures

[eaton-digital-nzm-brochure-br013003en-en-us.pdf](#)

[eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf](#)

### Catalogs

[eaton-digital-nzm-catalog-ca013003en-en-us.pdf](#)

### Declarations of conformity

[DA-DC-03\\_NZM2](#)

### Drawings

[eaton-circuit-breaker-switch-nzm-mccb-dimensions-008.eps](#)

[eaton-circuit-breaker-mounting-nzm-mccb-3d-drawing.eps](#)

### Installation instructions

[eaton-side-wall-actuator-nzm2-xzb-xs-il01206004z.pdf](#)

### Installation videos

[The new digital NZM Range](#)

[Introduction of the new digital circuit breaker NZM](#)

### mCAD model

[DA-CS-nzm2\\_xs\\_r\\_m\\_r](#)

[DA-CD-nzm2\\_xs\\_r\\_m\\_r](#)

### Technical data sheets

[eaton-nzm-technical-information-sheet](#)

#### 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

#### 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.2.7 Inscriptions

Meets the product standard's requirements.

#### 10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.4 Clearances and creepage distances

Meets the product standard's requirements.

#### 10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

#### 10.8 Connections for external conductors

Is the panel builder's responsibility.

#### 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

#### 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

#### 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

#### Color

Black

#### Fitted with:

Black and yellow lightning symbol

Special short extension shaft

Door coupling rotary handle

Extension shaft

Mounting brackets

External warning plate/markings plate in German/English

Padlock

#### Frame

NZM2

#### Activation type

Actuation on the right

#### Suitable for

Power circuit breaker

Switch disconnectors

#### Cover/door type

Door interlock lockable in 0 position on handle

Door interlock can also be modified in I position

Door interlock extension cannot be used.

Narrowest minimum clearance between enclosure side plates of control panel and circuit breaker is defined by mounting bracket.

#### Degree of protection / NEMA enclosure type

IP66

4X. 12



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia