


Technical Data Sheet:	DS572/1212	FLEXIC	DN	
Product Description	Straight, fixed, external thread, Stain- less Steel, SSU conduit fitting.	FLEXIBLE CONDUIT SOLUTIONS		
Product Range	SSU - M Type Stainless Steel fitting	Roman Way, Coleshill Birmingham B46 1HC, United Kingdom		
	(Metric Threads)	B46 1HG, United Kingdom Tel: 00 44 (0)1675 466900 Website: www.flexicon.uk.com		







							Applications:	
Conduit	Part No.	Metric Thread	Dimension (mm)		n)	Suitable for knockouts.		
Size		A	В	С	D	E	Two part fitting comprising of shell and body.	
10	SSU10-M12-M	M12 X 1.5	8.0	5.6	21.0	14.0		
12	SSU12-M16-M	M16 X 1.5	8.0	8.5	23.0	19.0	Features:	
16	SSU16-M16-M	M16 X 1.5	10.0	11.5	25.0	19.0	High tensile strength	
20	SSU20-M20-M	M20 X 1.5	10.0	15.3	26.3	24.0	Oil resistant Corrosion resistant	
25	SSU25-M25-M	M25 X 1.5	10.0	19.1	32.5	28.6	Conforms to EN 61386	
32	SSU32-M32-M	M32 X 1.5	13.0	26.2	36.8	38.0	Note: also available in Nickel Plated Brass	
40	SSU40-M40-M	M40 X 1.5	14.0	34.6	39.0	48.0	versions and swivel versions.	
50	SSU50-M50-M	M50 X 1.5	15.0	44.7	44.5	58.0	Temperature	
63	SSU63-M63-M	M63 X 1.5	18.0	53.9	50.5	70.0	Performance:	
							100% 0 10 1 100% 0	









IEC EN 61386



CE

EN 61386 Classification Available on request


COMPLIANT TO LUL STANDARD 1-085-A3

London Underground Certificate No. 296

Typical Applications;







Temperature Performance:

Material:

Colour:

Self colour

Hazard

INHEREN[®] LOW FIRE **AZARI**

IP Rating:

• IP40

Stainless Steel (Grade 316)

Fire Performance: Inherently Low Fire

-100°C to +400°C

Errors, omissions and amendments excepted. As part of continuing product development Flexicon Ltd reserve the right to alter product specifications without prior notice. Data given is correct at time of compilation. Product specification and application data is for guidance only and does not constitute a warranty of any kind, either expressed or implied for Flexicon products or their suitability for a specific purpose. Third party approvals maybe limited to certain sizes within a product range.

Created by;	Approved by;	Date;	Page Number;
Colin Legg - Marketing Manager	Ian Gibson - Technical Director	December 2012	Page 1 of 1