

THROUGH CONNECTORS L37-M

□

L-M range of connectors are designed for jointing low voltage conductors. Made of electrolytic copper tube having the same dimension as A-M series lugs: L-M connectors are annealed and electrolytically tin plated. They feature an internal taper at both ends to ease the introduction of the conductor and a central stop to ensure correct positioning.

L-M series lugs are manufactured from electrolytic copper tube Cu-OF CW008A conform to UNI EN 13600.

Certificates

□ E125401

THROUGH CONNECTORS L37-M

Technical characteristics

	Properties
Length	2.52 in.
Diameter	0.76 in.
Pack qty	30
Min. pack qty	15
Maximum diameter of the stripped cable	0.76 in.
Material (Body)	ETP Copper elettrolyticaly tinned
Material (Seam)	ETP Copper elettrolyticaly tinned

□ □

THROUGH CONNECTORS L37-M

Products used together

Tools

18.0 V CORDLESS HYDRAULIC CRIMPING TOOL B1300-C - B1300-CA
18.0 V CORDLESS HYDRAULIC CRIMPING TOOL B550 - B550CA
HYDRAULIC CRIMPING TOOL HT120 - HT120
HYDRAULIC CRIMPING TOOL HT131LN-C - HT131LN-C
HYDRAULIC CRIMPING TOOL HT51 - HT51
HYDRAULIC PRESSHEAD RHC131LN - RHC131LN
HYDRAULIC PRESSHEAD RHU131-C - RHU131-C
HYDRAULIC PRESSHEADS RH50 - RH50
HYDRAULIC PRESSHEADS RHU520 - RHU520
18.0 V Cordless hydraulic crimping tool B1300-C-KV - B1300-CA-KV
18V Cordless Hydraulic Crimping Tool B500ND - B500NDA
HYDRAULIC CRIMPING TOOL HT131-C - HT131-C
HYDRAULIC CRIMPING TOOL HT131-UC - HT131-UC
HYDRAULIC PRESSHEAD RHC131 - RHC131
HYDRAULIC PRESSHEAD RHM132 - RHM132
HYDRAULIC PRESSHEADS ECW-H3D - ECW-H3D
HYDRAULIC PRESSHEADS RHM50 - RHM50
INSULATED HYDRAULIC PRESSHEAD RHC131LN-KV - RHC131LN-KV