

SACC-BP-M-M12-THR PP - Housing screw connection



1027661

<https://www.phoenixcontact.com/gb/products/1027661>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Housing screw connection, Pin, M12-Push-pull external locking, Rear mounting, M15 x 1, THR- und Wellenlötkontakte, Item is lead-free in accordance with RoHS II without Exemption 6c (Pb < 0.1 %)

Your advantages

- Manufacturer-independent M12 push-pull locking system for maximum availability
- Easy and quick cabling of devices and systems in hard-to-reach areas
- Easy device integration, thanks to mechanical port screw connections with threaded fastening
- Flexible PCB assembly: two-piece connectors for wave and THR soldering

Commercial data

| | |
|--------------------------------------|---------------|
| Item number | 1027661 |
| Packing unit | 20 pc |
| Minimum order quantity | 20 pc |
| Sales key | ABQCCA |
| Product key | ABQABA |
| GTIN | 4055626533360 |
| Weight per piece (including packing) | 12.69 g |
| Weight per piece (excluding packing) | 11.073 g |
| Customs tariff number | 79070000 |
| Country of origin | DE |

Technical data

Notes

| | |
|--------------------|--|
| Notes on operation | The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration. |
| Order information: | Lock nut is included in the scope of delivery |

Product properties

| | |
|--------------|---------------------|
| Product type | Panel mounting base |
| Thread type | M12 |

Connection data

| | |
|-------------------|----------------------------|
| Connection method | THR- und Wellenlötkontakte |
| Tightening torque | 1.5 ... 2 Nm |

Material specifications

| | |
|--|----------------------|
| Material | Brass, nickel-plated |
| Flammability rating according to UL 94 | V0 |
| Seal material | EPDM |
| Material for screw connection | Brass, nickel-plated |

Connector

Connection 1

| | |
|-------------------|----------------------------|
| Head design | Pin |
| Head thread type | M12 |
| Head locking type | Push-pull external locking |

Mechanical properties

Mechanical data

| | |
|-----------------------------|-------|
| Insertion/withdrawal cycles | > 100 |
|-----------------------------|-------|

Environmental and real-life conditions

Ambient conditions

| | |
|--|---|
| Degree of protection (when plugged in) | IP67 (correctly plugged in and locked) |
| Degree of protection | IP67 (correctly plugged in and locked) IP67, when in locked state |
| Ambient temperature (operation) | -25 °C ... 85 °C (Plug / socket) -40 °C ... 85 °C (without mechanical actuation) |
| UL Type Rating | Type 4 (indoor use only) |

SACC-BP-M-M12-THR PP - Housing screw connection



1027661

<https://www.phoenixcontact.com/gb/products/1027661>

Standards and regulations

| | |
|--------------------------|--------------------------|
| Standard designation | M12 circular connector |
| Standards/specifications | based on IEC 61076-2-010 |
| Note | Push-pull |

Mounting

| | |
|---------------|---|
| Mounting type | Rear mounting M15 x 1 Spacing between the top edge of the PCB and the back of the front plate: 6 mm |
| Assembly note | Spacing between the top edge of the PCB and the back of the front plate: 6 mm |

SACC-BP-M-M12-THR PP - Housing screw connection



1027661

<https://www.phoenixcontact.com/gb/products/1027661>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-13.0 | 27440224 |
|-------------|----------|

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC003556 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

SACC-BP-M-M12-THR PP - Housing screw connection



1027661

<https://www.phoenixcontact.com/gb/products/1027661>

Environmental product compliance

EU RoHS

| | |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|

China RoHS

| | |
|--|--|
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |

EU REACH SVHC

| | |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

Phoenix Contact 2025 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk