SIEMENS

Data sheet 6GT2690-0AH00

product type designation

product description

quick-change chuck MDS D139, D339

Support for mounting heat-resistant transponders with 20 mm distance to metal MOBY D/RF300 ISO Quick change holder Stainless steel for MDS D139 and MDS D339; Mounting with nut M8; Packing unit: 10 units.



suitability for use	The support is mounted via M8 nuts, whereas the transponder is held by a
	splint. The splint allows the transponder to be quickly removed from the
	support.

suitability for operation	for holding the transponders MDS D139/D339
mechanical data	
material	Stainless steel
color	metallic
ambient conditions	
ambient temperature	
during operation	-40 +220 °C
 during storage 	-40 +220 °C
 during transport 	-40 +220 °C
design, dimensions and weights	
height	60 mm
diameter	22 mm
net weight	80 g
further information / internet links	

internet link

• to website: TIA Selection Tool

• to web page: selection aid TIA Selection Tool

• to the website: IWLAN

• to website: Industrial communication

• to website: Industry Mall

• to website: Information and Download Center

• to website: Selection guide for cables and connectors

• to website: Image database

• to website: CAx-Download-Manager

• to website: Industry Online Support

http://www.siemens.com/tia-selection-tool

https://support.industry.siemens.com/cs/ww/en/view/67384964

http://www.siemens.com/iwlan

http://www.siemens.com/ident/rfid

https://mall.industry.siemens.com

http://www.siemens.com/industry/infocenter

https://sie.ag/2QdlxcP

http://automation.siemens.com/bilddb

http://www.siemens.com/cax

https://support.industry.siemens.com

11/9/2023 last modified:

