Product datasheet

Specifications

Harmony XB5, Legend plate 30 x 50 mm, metal

ZBYM6101

EAN Code: 3606489756000

Main

Product or component type	Legend plate
Accessory / separate part category	Marking accessory

Complementary

Material	Metal
Device composition	Blank legend Legend plate
Accessory / separate part destination	Ø 22 mm control or signalling unit with square head Ø 22 mm control or signalling unit with circular head For standard head
Range compatibility	Harmony XB4 Harmony XB5
Legend holder size	30 x 50 mm
Marking	unmarked

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.000 cm
Package 1 Width	0.100 cm
Package 1 Length	15.000 cm
Package 1 Weight	6.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	11.000 cm
Package 2 Width	0.100 cm
Package 2 Length	15.000 cm
Package 2 Weight	61.000 g
Unit Type of Package 3	S01
Number of Units in Package 3	200
Package 3 Height	15.000 cm
Package 3 Width	15.000 cm
Package 3 Length	40.000 cm

| **Package 3 Weight** | 1.632 kg |

Logistical informations

| **Country of origin** | FR |

Contractual warranty

| **Warranty** | 18 months |

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained 〉

How we assess product sustainability 〉

Use Better

Materials and Substances	
Packaging without single use plastic	**No**
China RoHS Regulation	**China RoHS declaration**

Use Again

Repack and remanufacture	
Take-back	**No**

Offer Marketing Illustration

Product benefits / Features

Offer Marketing Illustration

Product benefits / Features

Technical Benefits
Harmony XB5

Conformity with IEC, UL, CSA, CCC EAC, and JIS standards, as well as CE marking and marine approvals

Up to IP66, 67, 69, 69K, and type 4X protection ratings

High vibration resistance with shake-proof terminal screws

Operating temperature from -40°C –to 70°C

Shock protection level up to IK06

Secure switching of inductive or heavy DC loads directly – 100 000 operations at 10A, 24V dc

Image of product / Alternate images

Alternative