

Professionally approved products.
Datasheet
SINGLE POLE TERMINAL BLOCKS
Indirect clamping



Professionally approved products. Datasheet

| Stock no. | No of ways | Connecting Capacity sqmm | Nominal Voltage V | Maximum Operating Temperature °C | Insulation Specification | Self Extinguishing Specification | Dimensions mm | Weight g |
|-----------|------------|--------------------------|-------------------|----------------------------------|------------------------------------|----------------------------------|---------------|----------|
| 388-2833 | 12 | (10 way) 6 | 450 | 85 | IP20 | V-0 (UL94) | 104.5x50xh42 | 125 |
| 315-4920 | 6 | (4 way) 16 | 450 | 85 | IP21 | V-0 (UL94) | 83x49xh52 | 140 |
| 388-2811 | 6 | (6 way) 1÷6 | 450 | 85 | IP22 | V-0 (UL94) | 23x53xh34 | 31 |
| 315-4807 | 3 | (3 way) 1÷6 | 450 | 85 | IP23 | V-0 (UL94) | 23x40xh36.5 | 18.5 |
| 388-2827 | 8 | (6 way) 6 | 450 | 85 | IP24 | V-0 (UL94) | 35.5x57xh42 | 56 |
| 315-4841 | 3 | 16 | 450 | 85 | IP25 | V-0 (UL94) | 38x50xh44 | 55.5 |
| 315-4908 | 3 | 35 | 450 | 85 | IP26 | V-0 (UL94) | 53x54xh56 | 114 |
| 315-4835 | 5 | (5 way) 1÷6 | 450 | 85 | IP27 | V-0 (UL94) | 35x40xh36.5 | 26.5 |
| 315-4863 | 5 | 16 | 450 | 85 | IP28 | V-0 (UL94) | 61x50xh44 | 68 |
| | | | | | D= Version with clamp for DIN rail | | | |