

**Dimensions**

mm  
inch

**KG-Switches**

**Mounting**  
(Additional length for auxiliary contacts see page 36)

**On/Off Switches 3 pole**

<b>VE</b>		<b>A</b>	<b>B</b>	<b>C</b>	<b>D1</b>	<b>D2</b>	<b>D3</b>	<b>E1<sup>1)</sup></b>	<b>E2<sup>1)</sup></b>	<b>E3<sup>1)</sup></b>	<b>F</b>	<b>G</b>	<b>H</b>	<b>L</b>	<b>M</b>
	KG10A	48	36	12	8	5	5	60	65	50	22	48	50	49,2	-
		1.89	1.42	.47	.31	.20	.20	2.36	2.56	1.97	.87	1.89	1.97	1.94	-
	KG10B	64	48	27	10	5	5	60	65	50	22	48	50	56,2	-
		2.52	1.89	1.06	.39	.20	.20	2.36	2.56	1.97	.87	1.89	1.97	2.21	-
	KG20, KG32	30	-	12	8	3,2	5	60	-	-	22	42	54	50	20
		1.18	-	.47	.31	.13	.20	2.36	-	-	.87	1.65	2.13	1.97	.79
	KG41, KG64	48	36	12	10	5	5	70	-	-	25	50	64	61	-
		1.89	1.42	.47	.39	.20	.20	2.76	-	-	.98	1.97	2.52	2.40	-
	KG41B, KG64B	64	48	13,5	10	5	5	70	-	-	25	50	64	61	-
		2.52	1.89	.53	.39	.20	.20	2.76	-	-	.98	1.97	2.62	2.40	-
	KG80, KG100	64	48	13,5	10	5	6	90	-	-	25	70	80	68	-
		2.52	1.89	.53	.39	.20	.24	3.54	-	-	.98	2.76	3.15	2.68	-
	KG80C, KG100C	88	68	13,5	10	6	6	90	-	-	25	70	80	68	-
		3.46	2.68	.53	.39	.24	.24	3.54	-	-	.98	2.76	3.15	2.68	-

<b>VE/VE24</b>		<b>A</b>	<b>B</b>	<b>C</b>	<b>D1</b>	<b>D2</b>	<b>D3</b>	<b>G</b>	<b>H</b>	<b>L</b>	<b>N</b>	<b>P</b>	<b>Q1</b>	<b>Q2</b>
	KG125, KG160	88	68	16	13	6	6,4	112	108	91	-	36	59 - 61	59 - 61
		3.46	2.68	.63	.51	.24	.25	4.41	4.25	3.58	-	1.42	2.32 - 2.4	2.32 - 2.4
	KG250, KG315	88	68	5,5	13	6	6,4	145	126	98	-	44	70 - 72	70 - 72
		3.46	2.68	.22	.51	.24	.25	5.71	4.96	3.85	-	1.73	2.76 - 2.83	2.76 - 2.83
	KG126, KG161	88	68	16	13	6	6,4	112	110	91	45	36	38 - 40	38 - 40
		3.46	2.68	.63	.51	.24	.25	4.41	4.33	3.58	1.77	1.42	1.5 - 1.57	1.5 - 1.57
	KG251, KG316	88	68	5,5	13	6	6,4	145	126	98	50	44	40 - 42	40 - 42
		3.46	2.68	.22	.51	.24	.25	5.71	4.96	3.85	3.94	1.73	1.57 - 1.63	1.57 - 1.63
	KG127, KG162	188	68	16	13	6	6,4	112	109	91	45	36	38 - 40	59 - 61
		3.46	2.68	.63	.51	.24	.25	4.41	4.29	3.58	1.77	1.42	1.5 - 1.57	2.32 - 2.4
	KG252, KG317	88	68	5,5	13	6	6,4	145	126	98	50	44	40 - 42	70 - 72
		3.46	2.68	.22	.51	.24	.25	5.71	4.96	3.85	1.97	1.73	1.57 - 1.63	2.76 - 2.83

<b>VE/VE24</b>		<b>A</b>	<b>B</b>	<b>L</b>	<b>N</b>	<b>P</b>	<b>D2</b>	<b>D3</b>
	KG125, KG160, KG250, KG315	88	68	112	108	91	36	59 - 61
	KG126, KG161, KG251, KG316	88	68	110	110	91	45	38 - 40
	KG127, KG162, KG252, KG317	188	68	109	109	91	45	38 - 40

<b>VE2</b>		<b>A</b>	<b>B</b>	<b>L</b>	<b>VE21</b>		<b>S</b>	<b>Number of Contacts</b>
	KG20A, KG32A	43,7	45,4	56,5		26,5	44	up to 4
		1.72	1.79	2.22		104	46	up to 6
	KG41, KG64	52,4	45,4	56,5		52,3	1.81	up to 8
	2.06	1.79	2.22	206	54	2.13		
KG80, KG100	70	45	65					
	2.76	1.77	2.56					

1) Switches KG10A and KG10B allow use of E1, E2 or E3.