

Auxiliary contact, Acti9 A9N, OF, 1 C/O, 2mA to 100mA, 24VAC to 250VAC, 24VDC to 220VDC, bottom connection

A9N26914

EAN Code: 3606482129184

Main

range of product	Acti9	
Product or component type	OC contact	
Device short name	OF	
Signal contacts composition	1 C/O	
[In] rated current	2100 mA at 24240 V, AC 50/60 Hz 2100 mA at 24 V, DC 2100 mA at 48 V, DC 2100 mA at 60 V, DC 2100 mA at 130 V, DC 2100 mA at 220 V, DC	
9 mm pitches	1	
Standards	EN/IEC 60947-5-1 EN/IEC 60947-5-4 GB/T 14048.5 GB/T 14048.17	
Product certifications	CE UKCA	
Quality labels	EAC CCC	

Complementary

Operating mode	Daisy chain up to 100 devices	
[Ui] rated insulation voltage	500 V	
[Uimp] rated impulse withstand voltage	4 kV	
Mounting mode	Clip-on	
Mounting location	Left side of circuit-breaker	
Mounting support	DIN rail	
Comb busbar and distribution block compatibility	Top: YES	
Height	85.3 mm	
Width	9 mm	
Depth	68 mm	
Net weight	30 g	
Colour	White	
Connections - terminals	Screw clamp terminal (bottom) 1 cable(s) 0.52.5 mm² - rigid Screw clamp terminal (bottom) 2 cable(s) 1.5 mm² - flexible Screw clamp terminal (bottom) 2 cable(s) 1.5 mm² - flexible with ferrule	

Wire stripping length	9 mm
Tightening torque	1 N.m bottom

Environment

IP degree of protection	IP20
Pollution degree	3
Tropicalisation	2
Ambient air temperature for operation	-2570 °C
Ambient air temperature for storage	-4085 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.000 cm
Package 1 Width	7.700 cm
Package 1 Length	9.500 cm
Package 1 Weight	38.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Height	8.500 cm
Package 2 Width	10.000 cm
Package 2 Length	23.500 cm
Package 2 Weight	514.000 g
Unit Type of Package 3	S03
Number of Units in Package 3	120
Package 3 Height	30.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	5.779 kg

Logistical informations

Country of origin CN

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	1
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins