

500/350/250/150MHz DIGITAL STORAGE OSCILLOSCOPE



The IDS-3000 Series digital storage oscilloscope is a full-featured and powerful tool that allows you to tackle complex measurement issues with ease. The IDS-3000 Series, carrying a maximum bandwidth of 500MHz, is equipped with a real-time sampling rate up to 5GSa/s and an equivalent-time sampling rate of 100GSa/s. The large 8-inch SVGA TFT LCD screen, combined with the advanced digital signal processing technology – VPO, provides meticulous detail and clarity for the displayed waveforms. The IDS-3000 Series gives you confidence not to miss any part of the test signal in the product verification and debugging stages and allows you to speed up your task without hesitation.

Rich Features

With widespread applications of embedded system using serial bus communications, resolving unexpected issues, such as propagation delay and bus contention, is often a challenge to design and testing engineers. The IDS-3000 Series provides (optional) design and testing engineers with powerful tools for the communication analysis and debugging of the most popular serial interface projects including I²C, SPI and UART. To fulfill the increasing power measurement demands, as a green energy trend, IDS-3000 provides an embedded power-measurement software (optional), which includes measurements of Power Quality, Harmonics, Ripple and Inrush Current, meeting requirements of most power measurement standards.

Hi-tech Platform

With 5GSa/s sampling and Visual Persistence Oscilloscope (VPO) technology, GDS-3000 displays waveforms truthfully and captures less-frequently-occurred signals, like glitches or runts, simultaneously without missing any spot of waveform information. A unique Split-screen feature allows each input channel to be operated independently with respective setting and waveform display. This gives users flexibility to use IDS-3000 Series as a multi-scope-in-one DSO. To alleviate the burden of manual operation and to reduce human error, additional features such as auto range are used to automatically adjust the horizontal and vertical scale of a displayed signal so that waveforms are displayed with the best possible viewing ratio. The I/O Interfaces give you a good range of choices and convenience. In the front panel, a USB host port is used for easy data access. And in the rear panel, another USB port can be used for remote control or for screen printout directly from PictBridge compatible printers. In addition, RS-232 and LAN interfaces provide the flexibility supporting broad range of applications. The SVGA video output port allows you to display the screen on an external projector or monitor for information sharing and discussion.

Unique Signal Processing -VPO

The IDS-3000 Series VPO (Visual Persistence Oscilloscope) technology adopts a very unique signal-processing design. To significantly increase the data processing speed and the waveform capture rate, IDS-3000 Series uses FPGA platform to replace conventional serial microprocessor architecture. This unique technology allows the IDS-3000 Series to show waveforms in a fashion like that of an analog oscilloscope. The VPO three dimension waveform display, containing the information of amplitude, time and duration, provides more useful signal contents for the analysis of rapid-changed events, such as video, jitter and infrequent signals.

IDS-3000 Series

FEATURES

- 500/350/250/150MHz Bandwidth
- Dual Sampling Modes: 5GSa/s Real-Time Sampling Rate and 100GSa/s Equivalent Time Sampling Rate
- 25k Points Memory for Each Input Channel
- VPO (Visual Persistence Oscilloscope) Technology to Display Less-Frequently-Occurred Signals
- 8" 800 x 600 High Resolution TFT LCD Display
- Unique Split Screen System with Independent Setting for Each Input Channel
- Three Input Impedance Selections: 50Ω/75Ω/1MΩ
- Optional Power Measurement Software for Power Supply Measurement and Analysis
- Optional Serial BUS Triggering and Decoding Software Supporting I²C, SPI and UART
- Support GW APP Software-Easy Upgrade of Feature New Function



Front



Rear Panel

APPLICATIONS

- Industrial and Educational R&D Labs
- Product Testing and Quality Assurance
- Power Supply and Serial BUS Design
- System Integration & Debugging
- Maintenance & Repair Service



IDS-3000 Series

SPECIFICATIONS									
VERTICAL	Channels	GDS-3152	GDS-3154	GDS-3252	GDS-3254	GDS-3352	GDS-3354	GDS-3552	GDS-3554
	Bandwidth	2Ch+EXT	4Ch+EXT	2Ch+EXT	4Ch+EXT	2Ch+EXT	4Ch+EXT	2Ch+EXT	4Ch+EXT
	Rise Time	DC~150MHz(-3dB) 2.3ns		DC~250MHz(-3dB) 1.4ns		DC~350MHz(-3dB) 1ns		DC~500MHz(-3dB) 700ps	
	Bandwidth Limit	20MHz		20M/100MHz		20M/100M/200MHz		20M/100M/200/350MHz	
	Vertical Resolution	The bandwidth of the 75 Ω input impedance is limited to 150MHz only							
	Vertical Resolution(1MΩ)	8 bits							
	Vertical Resolution(50/75 Ω)	2mV~5V/div							
	Input Coupling	2mV~1V/div							
	Input Impedance	AC, DC, GND							
	DC Gain Accuracy	1MΩ//15pF approx.							
Polarity	±(3% X Readout + 0.1div + 1mV)								
Maximum Input Voltage(1MΩ)	Normal , Invert								
Maximum Input Voltage(50/75Ω)	300V (DC+AC Peak), CAT I								
Offset Position Range	5 Vrms , CAT I								
Waveform Signal Process	2mV/div ~ 100mV/div : ±0.5V ; 200mV/div ~ 5V/div : ±25V								
TRIGGER	Source	Add, Subtract, Multiply, and Divide waveforms, FFT, FFTrms ; FFT : Spectral magnitude. Set FFT vertical scale to Linear RMS or dBV RMS, and FFT window to Rectangular, Hamming, Hanning or Blackman-Harris.							
	Trigger Mode	2CH model: CH1, CH2, Line , EXT ; 4CH model: CH1 , CH2 , CH3 , CH4 , Line , EXT							
	Trigger Type	Auto (Supports Roll Mode for 100 ms/div and slower), Normal, Single							
	Trigger Holdoff Range	Edge, Pulse Width, Video, Runt, Rise & Fall, Alternate, Event-Delay(1~65,535 events), Time-Delay(10ns~10s), I ² C, SPI, UART (optional)							
	Coupling	10ns ~ 10s							
EXT TRIGGER	Sensitivity	AC, DC, LF rej. , Hf rej. , Noise rej.							
		DC~30MHz Approx. 1div or 10mV; 50MHz~150MHz Approx. 1.5div or 15mV; 150MHz~350MHz Approx. 2div or 20mV; 350MHz~500MHz Approx. 2.5div or 25mV							
	Input Impedance	±15V							
HORIZONTAL	Range	DC ~ 150MHz Approx. 100mV							
	Sensitivity	150MHz ~ 250MHz Approx. 150mV;250MHz ~ 350MHz Approx. 150mV;350MHz~500MHz Approx. 200mV							
X-Y MODE	Pre-trigger Accuracy	1MΩ ±3%, ~16pF							
	Post-trigger Accuracy	1ns/div ~ 100s/div (1-2-5 increments; GDS-3502/3504 1-2-5-5 increments)ROLL : 100ms/div ~ 100s/div							
SIGNAL ACQUISITION	X-Axis Input/Y-Axis Input Phase Shift	10 div maximum							
		1,000 div max (depend on time base)							
		±20 ppm over any ≥ 1 ms time interval							
		Channel 1; Channel 3/Channel 2; Channel 4							
CURSORS AND MEASUREMENT	Real Time Sample Rate	2.5GSa/s	5GSa/s	2.5GSa/s	5GSa/s	5GSa/s	5GSa/s	4GSa/s	4GSa/s
	ET Sample Rate	100GSa/s maximum for all models							
	Record Length	25k points							
	Acquisition Mode	Normal, Average, Peak detect, High resolution, Single							
POWER MEASUREMENTS (OPTION)	Cursors	Average: 2 ~ 256 waveforms ; Peak detect: 2ns							
	Automatic Measurement	Amplitude, Time, Gating available							
	Cursors measurement	28 sets: Vpp , Vamp , Vavg , Vrms , Vhi , Vlo , Vmax , Vmin , Rise Preshoot/Overshoot , Fall Preshoot/Overshoot , Freq , Period , Rise time , Fall time , Positive width , Negative width , Duty cycle, Phase, and eight different delay measurements (FRR, FRF, FFR, FFF, LRR, LRF, LFR, LFF)							
	Auto counter	Voltage difference between cursors (ΔV) Time difference between cursors (ΔT)							
CONTROL PANEL FUNCTION	Power Quality Measurements	6 digits, range from 2Hz minimum to the rated bandwidth							
	Harmonics	VRMS, VCrest factor, Frequency, IRMS, ICrest factor, True power, Apparent power, Reactive power, Power factor, Phase angle.							
	Ripple Measurements	Freq, Mag, Mag rms, Phase, THD-F, THD-R, RMS							
	In-rush current	Wripple ,Iripple							
DISPLAY SYSTEM	Autoset	First peak, second peak							
	Auto-Range	Single-button, automatic setup of all channels for vertical, horizontal and trigger systems, with undo autoset							
	Save Setup	Allow automatically adjusts the time base and/or the vertical scale of displayed waveform when the frequency and/or the amplitude of input signal changed.							
	Save Waveform	20set							
INTERFACE	TFT LCD Type	24set							
	Display Resolution	8" TFT LCD SVGA color display(LED Back-light)							
	Interpolation	800 horizontal x 600 vertical pixels (SVGA)							
	Waveform Display	Sin(x)/x & Equivalent time sampling							
POWER SOURCE MISCELLANEOUS	Display Graticule	Dots, Vectors, Variable persistence, Infinite persistence							
	Display Brightness	8 x 10 divisions							
	RS-232C	Adjustable							
	USB Port	DB-9 male connector							
DIMENSIONS & WEIGHT	Ethernet Port	2 sets USB 2.0 high-speed host port ;1 set USB high-speed 2.0 device port							
	SVGA Video Port	RJ-45 connector, 10/100Mbps							
	GPIO	DB-15 female connector, monitor output for display on SVGA monitors							
	Go/NoGo BNC	GPIO-to-USB Adapter (Optional)							
	Internal Flash Disk	5V Max/10mA TTL open collector output							
	Kensington Style Lock	64MB							
	Line Output	Rear-panel security slot connects to standard Kensington-style lock							
		3.5mm stereo jack for Go/NoGo audio alarm							
	Line Voltage Range	AC 100V ~ 240V, 48Hz ~ 63Hz, auto selection							
	Multi-Language Menu	Available							
	On-Line Help	Available							
	Time clock	Time and date, provide the date/time for saved data							
		400(W) X 200(H) X 130(D)mm, Approx. 4 kg							

* Three-year warranty, excluding probes & LCD display panel. Specifications subject to change without notice. DS-3000GD1DH

ORDERING INFORMATION	
IDS-3552	500MHz, 2-Channel, Visual Persistence DSO
IDS-3554	500MHz, 4-Channel, Visual Persistence DSO
IDS-3352	350MHz, 2-Channel, Visual Persistence DSO
IDS-3354	350MHz, 4-Channel, Visual Persistence DSO
IDS-3252	250MHz, 2-Channel, Visual Persistence DSO
IDS-3254	250MHz, 4-Channel, Visual Persistence DSO
IDS-3152	150MHz, 2-Channel, Visual Persistence DSO
IDS-3154	150MHz, 4-Channel, Visual Persistence DSO
ACCESSORIES	
User manual x 1 ,Power cord x 1	
GTP-151R : 150MHz 10:1 passive probe for GDS-3152/3154 (one per channel)	
GTP-251R : 250MHz 10:1 passive probe for GDS-3252/3254 (one per channel)	
GTP-351R : 350MHz 10:1 passive probe for GDS-3352/3354 (one per channel)	
GTP-501R : 500MHz 10:1 passive probe for GDS-3502/35054 (one per channel)	

OPTION	
DS3-PWR	Power analysis software: Power quality/Harmonic/Ripple/In-rush current measurements
DS3-SBD	Serial Bus analysis software: I ² C/SPI/UART (only 4-channel models support SPI function)
GUG-001	GPIO to USB adapter
OPTIONAL ACCESSORIES	
GDP-025	25MHz High voltage differential probe
GDP-050	50MHz High voltage differential probe
GDP-100	100MHz High voltage differential probe
GCP-005	1kHz/5A Current probe
GCP-020	10kHz/200A Current probe
GCP-100	100kHz/100A Current probe
GCP-530	50MHz/30A Current probe
GCP-1030	100MHz/30A Current probe
GCP-206P	Power supply for current probe(2 input channel)
GCP-425P	Power supply for current probe(4 input channel)
GTP-033A	35MHz 1:1 Passive probe
GTP-352R	350MHz 20:1 Passive probe
CTC-001	Instrument cart 450(W)x30(D)mm(120V input socket)
GTC-002	Instrument cart 330(W)x30(D)mm(120V input socket)
GSC-008	SoR Carrying Case
GTL-110	Test lead, BNC to BNC connector
GTL-232	RS-232C cable, 9-pin female to 9-pin female, Null Modem for computer
GTA-411	USB 2.0 cable, A-B type cable 4P, 1800mm
GDB-03	Rack Adapter Panel
GKT-100	Oscilloscope Education and Training Kit
FREE DOWNLOAD	
PC Software	FreeWave software
Driver	USB driver ; LabView driver

ISO-TECH P. O. Box 99
Corby
Northants NN17 9RS
England
Tel: +44(0) 1536 201234