

XAPX2.E192925 - Temperature-indicating and -Regulating Equipment - Component

Note: We are enhancing our systems and you may notice duplicate entries/missing/outdated data. During this interim period, please contact our Customer Service at <https://www.ul.com/about/locations>.

Temperature-indicating and -Regulating Equipment - Component

HONEST-WELL CO LTD

4th Fl
4 Ln 560 Zhongzheng Rd
Xindian District
New Taipei, 23148 Taiwan

E192925

Marking: Company name or tradename "HW", "LC", and model designation.

Note: For additional marking information, refer to the [Guide Information Page](#).

Model(s): H2/11, H2/22, H2/31, H2/32, H2/33, H2K/11, H2M/11, H2M/33, H3/33, H4/11

Model(s): T24Axxxxxx-xx-CB where x can be a number up to 250, followed by alphanumeric, followed by C, H, R, B, D, L, K, P, X, V, F, E, A, U, M, S, G, O, or N, followed by F, K, R, T or L, followed by 1, 2, 3, 5, 6, 7, 8, or 9, followed by alphanumeric characters in two digits

Model(s): T24Axxxxxx-xx-CE where x can be a number up to 210, followed by alphanumeric, followed by C, H, R, B, D, L, K, P, X, V, F, E, A, U, M, S, G, O, or N, followed by F, K, R, T or L, followed by 1, 2, 3, 5, 6, 7, 8, or 9, followed by alphanumeric characters in two digits

Model(s): T24Axxxxxx-xx-CN where x can be a number up to 250, followed by alphanumeric, followed by C, H, R, B, D, L, K, P, X, V, F, E, A, U, M, S, G, O, or N, followed by F, K, R, T or L, followed by 1, 2, 3, 5, 6, 7, 8, or 9, followed by 35

Model(s): T24Axxxxxx-xx-PB where x can be a number up to 205, followed by alphanumeric, followed by C, H, R, B, D, L, K, P, X, V, F, E, A, U, M, S, G, O, or N, followed by F, K, R, T or L, followed by 1, 2, 3, 5, 6, 7, 8, or 9, followed by alphanumeric characters in two digits

Model(s): T24Axxxxxx-xx-TB where x can be a number up to 205, followed by alphanumeric, followed by C, H, R, B, D, L, K, P, X, V, F, E, A, U, M, S, G, O, or N, followed by F, K, R, T or L, followed by 1, 2, 3, 5, 6, 7, 8, or 9, followed by alphanumeric characters in two digits

Model(s): T24Bxxxxxx-xx-PB where x can be a number up to 205, followed by alphanumeric, followed by C, H, R, B, D, L, K, P, X, V, F, E, A, U, M, S, G, O, or N, followed by F, K, R, T or L, followed by 1, 2, 3, 5, 6, 7, 8, or 9, followed by alphanumeric characters in two digits

Model(s): T24Bxxxxxx-xx-TB where x can be a number up to 205, followed by alphanumeric, followed by C, H, R, B, D, L, K, P, X, V, F, E, A, U, M, S, G, O, or N, followed by F, K, R, T or L, followed by 1, 2, 3, 5, 6, 7, 8, or 9, followed by alphanumeric characters in two digits

Model(s): T24Mxxxxxx-xx-CB where x can be a number up to 250, followed by alphanumeric, followed by C, H, R, B, D, L, K, P, X, V, F, E, A, U, M, S, G, O, or N, followed by F, K, R, T or L, followed by 1, 2, 3, 5, 6, 7, 8, or 9, followed by alphanumeric characters in two digits

Model(s): T24Mxxxxxx-xx-PB where x can be a number up to 205, followed by alphanumeric, followed by C, H, R, B, D, L, K, P, X, V, F, E, A, U, M, S, G, O, or N, followed by F, K, R, T or L, followed by 1, 2, 3, 5, 6, 7, 8, or 9, followed by alphanumeric characters in two digits

Model(s): T24Mxxxxxx-xx-TB where x can be a number up to 205, followed by alphanumeric, followed by C, H, R, B, D, L, K, P, X, V, F, E, A, U, M, S, G, O, or N, followed by F, K, R, T or L, followed by 1, 2, 3, 5, 6, 7, 8, or 9, followed by alphanumeric characters in two digits

Appliance thermostats, Model(s): T26

Auto reset thermostat, Model(s): KSD301

Automatic, Temperature-Limiting Thermostats investigated to UL 873, Model(s): T23A followed by 050 through 220, followed by A or B, followed by A, B, C, D, H, P, R, S, X, L, K, V, F, E, U, M, G, N, or O, followed by F, K, R, T, or L, followed by 1, 2, 3, 5, 6, 7, 8, or 9, followed by 10 through 30, M5, M6, or M7.

Automatic, Temperature-Limiting Thermostats investigated to UL 873, Model(s): T23B followed by 050 through 220, followed by A or B, followed by A, B, C, D, H, P, R, S, X, L, K, V, F, E, U, M, G, N, or O, followed by F, K, R, T, or L, followed by 1, 2, 3, 5, 6, 7, 8, or 9, followed by 10 through 30, M5, M6, or M7.

Manual, Temperature-Limiting Thermostats investigated to UL 873, Model(s): T23M followed by 050 through 220, followed by A or B, followed by A, B, C, D, H, P, R, S, X, L, K, V, F, E, U, M, G, N, or O, followed by F, K, R, T, or L, followed by 1, 2, 3, 5, 6, 7, 8, or 9, followed by 10 through 30, M5, M6, or M7.

Last Updated on 2021-12-02

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"