

CERTIFICATE OF COMPLIANCE

Certificate Number 20141030-E28476
Report Reference E28476-20141028
Issue Date 2014-OCTOBER-30

Issued to: TYCO ELECTRONICS CORP
2901 FULLING MILL RD
MIDDLETOWN PA 17057

**This is to certify that
representative samples of**

COMPONENT - CONNECTORS FOR USE IN DATA,
SIGNAL, CONTROL AND POWER
APPLICATIONS

Component Connector, Cat. No. 5787444,
followed by 1 or 2

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety:

UL 1977 - Component Connectors for Use in Data, Signal,
Control and Power Applications,
CAN/CSA C22.2 No. 182.3-M1987- Special Use
Attachment Plugs, Receptacles, and Connectors

Additional Information:

See the UL Online Certifications Directory at
www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's
Certification and Follow-Up Service.

Recognized components are incomplete in certain constructional features or restricted in performance
capabilities and are intended for use as components of complete equipment submitted for investigation rather
than for direct separate installation in the field. The final acceptance of the component is dependent upon its
installation and use in complete equipment submitted to UL LLC.

Look for the UL Certification Mark on the product.

B. Mahrenholz

Bruce Mahrenholz, Assistant Chief Engineer, Global Inspection and Field Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please
contact a local UL Customer Service Representative at www.ul.com/contactus



DESCRIPTION

PRODUCT COVERED:

USR, CNR Component Connector, Cat. No. 5787444, followed by 1 or 2.

GENERAL:

These devices are multi-pole connectors intended for factory assembly on where the acceptability of combinations is determined by UL LLC. The devices are identified as follows:

USR indicates investigation to United States Standards, UL 1977.

CNR indicates investigation to Canadian National Standards, C22.2 No. 182.3.

RATINGS:

Series No.	Voltage, Vac/Vdc	Current, A
5787444	-	-

Disconnecting Use - Optional, see Sec Gen for required marking

TECHNICAL CONSIDERATIONS (NOT FOR FIELD REPRESENTATIVE'S USE):

Use - For use only in or with complete equipment where the acceptability of the combination is determined by UL LLC.

Conditions of Acceptability - The following are among the considerations to be made when evaluating the device in the end-use product.

Interruption of Current

1. These devices are not suitable for interrupting the flow of current by connecting or disconnecting the mating connector.

Current-Carrying Capability and Current Ratings

2. These devices have not been subjected to the Temperature test and as a result do not have an assigned current rating. The device's current carrying capability is to be reviewed in the end-use by measuring temperatures on the connector housing and/or terminals when current is flowing through the connector under conditions of normal use.

Insulating Materials

3. These devices employ insulating materials with properties as tabulated below at the minimum thickness employed in the connector housing, the suitability of the insulating materials based on the documented values shall be determined in the end-use application. Please note the values specified in the table when multiple materials are indicated represent the minimum values for the group of materials.

Series No.	Insulating Material (#)	Measured Minimum Thickness	Flame Class	HWI	HAI	RTI Elec	Max Operating Temp, °C
5787444	A	1.4 mm	V-0	0	0	130	130

(#) - Code for Insulating Body Material.

- * A. TYCO RM# 704556.
 1. Dielectric strength (kV/mm): 23
 2. CTI: 1

Terminations

4. The terminals have not been evaluated for compliance with the dimensional requirements of UL 310, the Standard for Electrical Quick-Connect Terminals and CSA C22.2 No. 153, Quick-Connect Terminals.

Miscellaneous

5. The enclosure of the device has live parts that may be exposed to user contact when the connector is energized. The device is suitable for use only within an acceptable enclosure.