CDS 400 S

Dial torque wrench

0.8 - 2000 Nm / 7 lbf·in - 1500 lbf·ft / with signal

Code
7652280

ETIM
EC002132

EAN
4002805304402

UNSPSC
27-11-17-15

Country of origin
Germany

eCl@ss
21-04-02-22

Customs tariff number
82041100

Article description

• Use:
• Controlled tightening and verification of tightening values
• For use in almost all industrial manufacturing areas
• Working ranges from 0.8 - 2000 Nm / 7 lbf·in - 1500 lbf·ft are covered
• Features:
• Dial-indicating torque wrench with dual scale and slave pointer
• 1/4", 3/8", 1/2", 3/4" or 1" double square drive with ball lock for controlled right and left tightening
• Models No. ADS 4 to No. ADS 40: With integrated ratchet function
• For controlled screw tightening and torque measurements
• Display accuracy: +/- 4 % tolerance of the indicated value
• Acc. to DIN EN ISO 6789, traceable to national standards
• With dual scale in Nm and lbf·in or lbf·ft double-tinted clearly readable face
• Built-in overload protection – mechanical stop up to a maximum of 25% overload of the maximum value
• Housing made of light, robust special aluminium construction - painted silver-grey
• Black, non-slip rubber handgrips
• Model No. ADS 4 to No. ADS 40: EPA (Electrostatic Protected Area) compliant, for use in electrostatically sensitive applications• • With audio-visual signal
• Test certificate acc. to DIN EN ISO 6789

Article information

Contents (Qty of pieces)	1
Net weight [kg]	3,2 kg
Total length [mm]	710 mm
Total height [mm]	111 mm
Drive connector square (male)	3/4"
Drive connector square (male)	20 mm
Drive type/drive	Double square
Torque (min.) [N·m]	80 Nm
Torque (max.) [N·m]	400 Nm
Torque (min.) [lbf·ft]	60 lbf·ft
Torque (max.) [lbf·ft]	300 lbf·ft
Torque range (min./max.) [N·m]	80 Nm - 400 Nm
Torque range (min./max.) [lbf·ft]	60 lbf·ft - 300 lbf·ft
Graphic display	no
Epa-/Esd-Model	no
Fixed setting	no
Graduation	10
Graduation [lbf·ft]	10 lbf·ft
Graduation [n·m]	10 Nm
Evaluation software	no