

Endress+Hauser FTL50H-GTT2AD6G6C

Compact point level switch for liquids especially in the food and life sciences industry. FTL50H is used as an overfill prevention or as pump dry-run protector. Also suitable for hazardous areas.



Picture for reference only. Product appearance may vary based on configuration

The Liquiphant FTL50H is a point level switch for use in hazardous areas with all international certificates. Especially useable in the food and life sciences industry with hygienic certificates (3-A, EHEDG, ASME BPE). FTL50H offers functional safety SIL2/SIL3. Reliable measurement values, not affected by: changing media properties, flow, turbulences, gas bubbles, foam, vibrations or build-up.

Configuration of FTL50H-GTT2AD6G6C:

Approval:	G	ATEX II 1/2GD Ex ia IIC T6/IECEx zone0/1
Process Connection:	TT2	Ingold fitting 25x46mm, 316L
Probe Length; Type:	AD	Compact; Ra<0.3um/12uin
Electronics; Output:	6	FEL56; SIL NAMUR (L-H signal)
Housing; Cable Entry:	G6	F15 IP66/67 316L hygiene; M20 gland
Additional Option:	C	EN10204-3.1 material (316L wetted parts), inspection certificate

Alternative part number: FTL50H-7QX6/0