



Part Number : [5035000993](#)

Product Description : 2.50mm Pitch SD Memory Card Connector, 2.95mm Height, Normal Mount, Push-Push, with Detect, Protect and Anti-Card-Fly-Out Features

Series Number : 503500

Status : Active

Product Category : Memory / SIM Card Connectors



Documents & Resources

Drawings

[5035000993_sd.pdf](#)

3D Models and Design Files

[5035000993.dxf](#)

[5035000993_stp.zip](#)

Specifications

[SPK-502250-001-001.pdf](#)

[5035009200-SPK-200.pdf](#)

[5035000000-010.pdf](#)

Product Environment Compliance

Compliance

| | |
|--------------------|--|
| GADSL/IMDS | Not Relevant |
| China RoHS |  per SJ/T 11365-2006 |
| EU ELV | Not Relevant |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Not Contained per D(2024)7663-DC (21 Jan 2025) |
| EU RoHS | Compliant per EU 2015/863 |

Compliance Statements

- EU RoHS
- REACH SVHC

- Low-Halogen

Industry Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest

- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

Part Details

General

| | |
|--------------|--|
| Status | Active |
| Category | Memory / SIM Card Connectors |
| Series | 503500 |
| Description | 2.50mm Pitch SD Memory Card Connector, 2.95mm Height, Normal Mount, Push-Push, with Detect, Protect and Anti-Card-Fly-Out Features |
| Product Name | SD Card |
| Style | Push-Push |
| UPC | 191128387170 |

Electrical

| | |
|-------------------------------|-----------------|
| Current - Maximum per Contact | 0.5A |
| Shielded | Yes |
| Voltage - Maximum | 50V AC (RMS)/DC |

Physical

| | |
|--------------------------------|-------|
| Card Detection Switch | Open |
| Card Entry Location | Front |
| Circuits (Loaded) | 9 |
| Durability (mating cycles max) | 10000 |
| Ejector Button Side | N/A |

| | |
|--------------------------------|-----------------------|
| Material - Contact | Copper Alloy |
| Material - Plating Mating | Gold |
| Material - Plating Termination | Tin |
| Material - Shell | Stainless Steel |
| Net Weight | 1547.202/mg |
| Packaging Type | Embossed Tape on Reel |
| PCB Locator | No |
| PCB Retention | Yes |
| Pitch - Mating Interface | 2.50mm |
| Temperature Range - Operating | -25° to +85°C |
| Termination Interface Style | Surface Mount |

Mates With / Use With

Use with Part(s)

| Description | Part Number |
|-------------|-------------|
| Use With | SD Card |