

RENOLIT CX-HT 2

Description

RENOLIT CX-HT 2 is a lubricating grease based on a high quality calcium sulphonate complex soap with a special selection of base oils.

RENOLIT CX-HT 2 features excellent working stability, good anti-wear properties, extremely good EP resistance, and outstanding corrosion protection even in the presence of salt water.

RENOLIT CX-HT 2 contains a solid lubricant package to improve the anti-wear properties under boundary friction condition even under high loads.

Application

RENOLIT CX-HT 2 is used for lubrication of highly loaded, low speed plain and roller bearings, open gears and gear wheels.

RENOLIT CX-HT 2 is used where special requirements of wear and corrosion protection under high temperatures are demanded, e.g. in

- Wheel bearings in tunnel furnace cars
- Rotary kilns and mills
- Cement plants
- Coal and ore mills
- Assembly lines of diggers
- Open gear racks and spindle bearings
- Hot applications in brick, ceramic, gassy concrete and concrete industry

RENOLIT CX-HT 2 is also available as spray under the name **RENOLIT UNLOAD**.

Advantages

- High work resistance
- Good anti-wear properties
- Good corrosion protection
- Water resistant
- EP resistant

Shelf Life

The minimum shelf life is 36 months if the product is properly stored between 0°C and 40°C in its unopened original container in a dry place. The indication of a minimum shelf life does not include any guarantee of durability.

PI 5-3536e, Page 1, PM 5, 10/16UK

RENOLIT CX-HT 2

Characteristics

Properties	Unit	Data	Test Method
Colour	-	Black	-
Thickener	-	Calcium-sulphonate complex-soap	-
Dropping point	°C	≥ 270	IP 396
Worked penetration (Pw 60)	0.1 mm	265 - 295	DIN ISO 2137
Work resistance ΔP_w (100.000-60)	0.1 mm	≤ 40	DIN ISO 2137
NLGI grade	-	2	DIN 51 818
Corrosion protection properties (Emcor test)	degree of corr.	0 – 0	DIN 51 802
Four ball method, welding load	N	6500	DIN 51 350-4
Flow pressure at -20°C	hPa	≤ 1400	DIN 51 805-2
Base oil viscosity at 40°C at 100°C	mm ² /s	350 32,5	DIN 51 562-1
Temperature range short term	°C	- 20 up to +200 +220	-

PI 5-3536e, Page 2, PM 5, 10/16UK

FUCHS LUBRICANTS (UK) PLC
New Century Street, Hanley
GB-Stoke-on-Trent, Staffordshire, ST1 5HU

Tel +44-1782 -20 37 00
Fax +44-1782 -20 20 73
contact-uk@fuchs-oil.com



Health, Safety and Environment - information is provided for products in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products.

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products