

Product Search Data Sheet

Note: This datasheet may be out of date. <u>Please download the latest datasheet of NCU18WF104J6SRB from the official website of Murata Manufacturing</u> <u>Co., Ltd.</u>

1. Excellent solderability and high stability in environment

6. NCU series are recognized by UL/cUL (UL1434, File

https://www.murata.com/en-us/products/productdetail?partno=NCU18WF104J6SRB

Features

2. Excellent long time aging stability

4. Flow / Reflow soldering possible5. Lead is not contained in the product.

No.E137188).


3. High accuracy in resistance and B-constant

NCU18WF104J6SRB

In Production Recommended RoHS REACH AEC-

Appearance & Shape





Applications

Limited Usage	Automotive Grade
Other Usage	 Various engine control units ABS control unit High power devices (IGBT) Temperature compensation for various circuits required high temperature.

Packaging Information

Packaging	Specifications	Minimum Order Quantity
RB	180mm Paper Tape	4000



Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



Product Search Data Sheet

NCU18WF104J6SRB

Note: This datasheet may be out of date

Please download the latest datasheet of NCU18WF104J6SRB from the official website of Murata Manufacturing

Co., Ltd. https://www.murata.com/en-us/products/productdetail?partno=NCU18WF104J6SRB

Specifications

Resistance (25°C)	100κΩ
Resistance Value Tolerance (at 25°C)	±5%
B-Constant (25/50°C)	4250K
B-Constant (25/50°C) Tolerance	±2%
B-Constant(25/80°C)(Reference Value)	4303K
B-Constant(25/85°C)(Reference Value)	4311K
B-Constant(25/100°C)(Reference Value)	4334K
Max. Voltage	5V
Maximum Operating Current (25°C)	0.032mA
Typical Dissipation Constant (25°C)	1mW/°C
Operating Temperature Range	-40°C to 150°C
Size Code (in mm)	1.6x0.8mm
Size Code (in inch)	0.6x0.3inch
Shape	SMD
Mass	0.0047g

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering

Product Search Data Sheet




NCU18WF104J6SRB


Note: This datasheet may be out of date.

Please download the latest datasheet of NCU18WF104J6SRB from the official website of Murata Manufacturing

Co., Ltd. https://www.murata.com/en-us/products/productdetail?partno=NCU18WF104J6SRB







Resistance-Temperature Characteristics

Maximum Operating Voltage Reduction Characteristics

 This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
 This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

3 of 3