



Commercial Rubber

Natural rubber is a good general purpose gasket material. Recommended for use in less demanding situations with air, water, weak acids and alkalis.

The Klinger group has been recognised as the market leader in gaskets and sealing for over a century. Our research and development laboratories have investigated over 250 different fibre forms in the search for asbestos free alternatives. The search has resulted in a range of high quality and high performance asbestos free materials that have been proven in service.

Typical Applications

- Low pressure systems < 10 bar
- Plastic and GRP flanges
- Water service
- Applications of limited bolt load

Typical Properties

- | | |
|------------------------|----------------------|
| ▪ Polymer: | NA |
| ▪ Hardness | 65° Shore A |
| ▪ Specific Gravity | 1.50g/cm |
| ▪ Tensile strength: | 3.0N/mm ² |
| ▪ Elongation at Break: | 250% Min |
| ▪ Operating Temp.: | -25 to 80°C |

Head Office

KLINGER Ltd
Wharfedale Road
Euroway Trading Estate
Bradford BD4 6SG

Tel: 01274 688 222
Fax: 01274 688 549
www.klingeruk.co.uk
enquiries@klingeruk.co.uk

Klinger Runcorn

Tel: 01928 577 030
Fax: 01928 575 223

Klinger Immingham

Tel: 08449 676 778
Fax: 08449 676 779

Klinger Southampton

Tel: 02380 611 855
Fax: 02380 610 360

Klinger Middlesbrough

Tel: 01642 220 289
Fax: 01642 220 290

Klinger Aberdeen

Tel: 01224 772 962
Fax: 01224 772 953

Klinger Grangemouth

Tel: 01324 472 231
Fax: 01324 482 111

