

SPECIFICATIONS

DESCRIPTION	SPECIFICATIONS
Compatibility	Fits All MX FUEL Equipment
Charge Duration	90 min
Capacity	6.0 Ah
Fuel Gauge	Yes
REDLINK Intelligence	Yes

MXF XC406
MX FUEL REDLITHIUM
XC406 Battery Pack



DESCRIPTION	SPECIFICATIONS
Compatibility	Fits All MX FUEL Equipment
Charge Duration	55 min
Capacity	3.0 Ah
Fuel Gauge	Yes
REDLINK Intelligence	Yes

MXF CP203
MX FUEL REDLITHIUM
CP203 Battery Pack



DESCRIPTION	SPECIFICATIONS
Compatibility	Charges All MX FUEL Equipment
Charge Speed	Charges MX FUEL REDLITHIUM CP203 Battery
	Charges MX FUEL REDLITHIUM XC406 Battery
REDLINK Intelligence	Yes
On-Board Fan	Yes
Cell Voltage Monitoring	Yes
On-Board Indicator Light	Yes

MXF C
MX FUEL Charger





MILWAUKEE TOOL

Milwaukee Electric Tool Corporation
BROOKFIELD, WI 53005
USA
Tel: +1 (262) 781-3600 • Fax: +1 (262) 790-6333

Milwaukee Asia Office
29/F, Tower 2, Kowloon Commerce Centre,
51 Kwai Cheong Road, Kwai Chung, Hong Kong
Tel: +852-2492-2181 • Fax: +852-2490-4778

Distributed by:

9/12/2020

All data incl. service and warranty conditions as well as product range are subject to change without notice.
Pictures not binding. No liability for printing errors or mistakes. © 2020 Milwaukee Electric Tool Corporation.
All trademarks are owned by Techtronic Cordless GP unless otherwise stated.

www.milwaukeetool.asia

Milwaukee™

MX FUEL™

EQUIPMENT REDEFINED
TRADE FOCUSED
SYSTEM WIDE



ALL MX FUEL™ BATTERIES
FIT ALL MX FUEL™ EQUIPMENT





SAFER HANDHELD CORING



- AUTOSTOP Technology provides more control and prevents over-rotation during bind-up situations

POWER TO CORE 152MM HOLES IN REINFORCED CONCRETE



- POWERSTATE Brushless Motor delivers the power to core up to 152mm holes in reinforced concrete

EASIER CORING ANYWHERE



- LED Level and pressure gauge provide an easier coring experience

RUN-TIME



(5) 76MM HOLES IN 152MM CONCRETE WITH CP BATTERY



(18) 76MM HOLES IN BLOCK WITH XC BATTERY



(9) 76MM HOLES IN BLOCK WITH CP BATTERY

SPECIFICATIONS

DESCRIPTION	SPECIFICATIONS
Bit Capacity	152mm (6")
Spindle Size	1-1/4"-7, ½"G
Adapter Size	A-Rod (32.0mm)
Speed (low/high)	800/1,600 rpm

DESCRIPTION	SPECIFICATIONS
AUTO-STOP	Yes
Wet/Dry Coring	Yes
Weight (w/CP203 battery)	10.3 kg
Dedicated Accessory	Drill Stand (MXF DR255TV)

*Techtronic Asia Company Limited is not affiliated with any of the competitors' products that were tested.
The testing was conducted on 18 June 2020 against leading competitors' products.




FULL 350MM CAPACITY



- Cut more in a single pass

FASTER CUTS FROM START TO FINISH



- Less muscle effort to start with push button activation

NO GAS HEADACHES



- Zero emissions, along with less noise and vibration provide a safer workspace
- Eliminates wearable parts of a gas engine

RUN-TIME (W/ 2 XC BATTERIES)



4.3M IN CONCRETE
125MM DEPTH OF CUT



8 CUTS
203MM DUCTILE IRON PIPE



22 CUTS
203MM CINDER BLOCK

SPECIFICATIONS


DESCRIPTION	SPECIFICATIONS
Bit Capacity	350mm (14")
Cut Depth	125mm
Arbor Size	20mm/25.4mm/27mm
Blade Speed	5,370 rpm

DESCRIPTION	SPECIFICATIONS
On-Board Water Line	Yes
Weight (w/XC406 battery)	16.7 kg
Dedicated Accessory	Saw Cart (MXF COSC)

*Techtronic Asia Company Limited is not affiliated with any of the competitors' products that were tested.
The testing was conducted on 18 June 2020 against leading competitors' products.



MORE PRODUCTIVE LOWER VIBRATION




- POWERSTATE Brushless Motor delivers 50 ft-lbs of impact energy with less vibration
- 1,300 BPM

LIGHTER WEIGHT



- Easily maneuver and transport throughout the jobsite

2 TONS PER CHARGE



- Breaks a 305mm x 152mm x 12m trench with one MX FUEL REDLITHIUM XC406 Battery Pack

RUN-TIME (W/ 1 XC BATTERY)



12M TRENCH
305MM WIDE X 152MM DEEP



2 + SIDEWALK SLABS
1.5M X 1.4M X 15CM DEEP

SPECIFICATIONS

DESCRIPTION	SPECIFICATIONS
Chuck Size	28mm HEX
Impact Energy	64 J
Blows per Minute	1,300
Vibration	5.17m/s²

DESCRIPTION	SPECIFICATIONS
Buried Chisel Release	Yes
Soft Start	Yes
Weight (w/XC406 battery)	29.6 kg
Dedicated Accessory	Breaker Trolley (MXF DHT)

*Techtronic Asia Company Limited is not affiliated with any of the competitors' products that were tested.
The testing was conducted on 18 June 2020 against leading competitors' products.