


# Product datasheet

Specifications



## END FEED BOX 630A RIGHT SIDE CIRCUIT BREAKER PROTECTION

KSA630ABDD4

EAN Code: 3606485015811

### Main

Range of product	Canalis
Product name	KS
Device short name	KSA
Product compatibility	Canalis KSA busbar trunking 500...1000 A
Offer type	Advanced Rising main
Product or component type	Feed unit
Conductors material	Aluminium
[Ie] rated operational current	630 A
[Ue] rated operational voltage	230...690 V
Number of circuits	1
Busbar trunking polarity	3L + N + PE
Protection type	Circuit breaker protection
Control type	Rotary handle
Colour	White (RAL 9001)

### Complementary

Mounting location	Right
Mounting support	Busbar
Body material	Metal
Connections - terminals	Cable with lug Bars
Width	1229 mm
Depth	390 mm
Height	457 mm
Net weight	39.2 kg
Standards	IEC 61439-1 IEC 61439-6

### Environment

IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	39.9 cm
Package 1 Width	50 cm
Package 1 Length	123 cm
Package 1 Weight	44.86 kg

## Contractual warranty

Warranty (in months)	18
----------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

Yes

[EU RoHS Directive](#)

Compliant

REACH Regulation

[REACH Declaration](#)

Halogen-free status

Halogen free product

PVC free

Yes

Silicone-free

Yes

## Use Longer

### Lifetime extension

Repair

No

## Use Again

### Repack and remanufacture

End of life manual availability

No need of specific recycling operations

Take-back

No

WEEE Label

 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Dimensions Drawings

Dimensions

---

