



Main

| | |
|---|-------------------------------------|
| Range | Compact |
| Product name | Compact NSX DC |
| Product or component type | Switch disconnecter |
| Device short name | Compact NSX100NA DC PV |
| Poles description | 4P |
| Network type | DC |
| [Ue] rated operational voltage | 1000 V DC conforming to IEC 60947-3 |
| [Ie] rated operational current | DC-22A: 100 A DC 1000 V |
| [Ui] rated insulation voltage | 1000 V DC conforming to IEC 60947-3 |
| [Uimp] rated impulse withstand voltage | 8 kV conforming to IEC 60947-3 |
| [Ith] conventional free air thermal current | 100 A at 65 °C |
| [Icm] rated short-circuit making capacity | 2.5 kA switch-disconnector alone |
| Breaking capacity code | NA |
| Suitability for isolation | Yes conforming to IEC 60947-3 |
| Contact position indicator | Yes |
| Visible break | No |
| Utilisation category | DC-22A |
| Pollution degree | 3 conforming to IEC 60947-3 |







Complementary

| | |
|--|--|
| Control type | Toggle |
| Mounting mode | Fixed |
| Upside connection | Front |
| Downside connection | Front |
| [Icw] rated short-time withstand current | 2.5 kA during 1 s conforming to IEC 60947-3 |
| Mechanical durability | 10000 cycles conforming to IEC 60947-3 |
| Electrical durability | 1500 cycles 1000 V DC In conforming to IEC 60947-3 |
| Connection pitch | 35 mm |
| Height | 161 mm |
| Width | 140 mm |
| Depth | 186 mm |
| Net weight | 2.4 kg |

Environment

| | |
|-------------------------|------------------------------|
| Standards | EN/IEC 60947 UL 508 |
| Product certifications | EAC CCC |
| IP degree of protection | IP20 conforming to IEC 60529 |
| IK degree of protection | IK07 |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation |  REACH Declaration |
| EU RoHS Directive | Compliant  EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information |  Yes |
| China RoHS Regulation |  China RoHS Declaration |
| Environmental Disclosure |  Product Environmental Profile |
| Circularity Profile |  End Of Life Information |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|