

1000 piece

76 mm

PRODUCT-DETAILS

GSC175

2-PC OUTER SLV CONN BLUE I.D. 0.175



Container Information

Package Level 1 Units

Package Level 1 Width

Package Level 1 Height

General Information	
Extended Product Type	GSC175
Product ID	7TAI029060R0010
EAN	5414363114383
Catalog Description	2-PC OUTER SLV CONN BLUE I.D. 0.175
Long Description	Two Piece Outer Sleeve Connector for Hexagonal Range, Length 1/4 Inch/6.4mm, Inner Diameter .175 Inches/4.45mm, Outer Diameter .215 Inches/5.46mm, Color Blue, Soft Bronze, Tin Plated
Ordering	
Ordering EAN	5414363114383
	5414363114383 786210813820
EAN	
EAN	

	76 mm
Package Level 1 Depth /	3.5 in
Length	89 mm
Package Level 2 Units	10000 piece
Package Level 2 Width	7 in
	178 mm
Package Level 2 Height	4 in
	102 mm
Package Level 2 Depth /	16.25 in
Length	413 mm

Additional Information	
Brand / Label	Sta-Kon
Color	Blue
Effective Date	19680516
Material	Soft Bronze
Number of Batteries	0
Product Name	STA-KON AND CATAMOUNT TERMINAL
Product Type	Two-Piece Outer Sleeve Connector
Special Functions	Shielded cable grounding system made of 2 cylindrical sleeves (inner sleeve + outer sleeve), for solderless crimp connection. Outer sleeve for the Hexagonal Range (the outer sleeve is crimped with a hand tool and the result is a hexagonal-shaped crimp), for grounding shielded and coaxial cables. The sleeves are color coded according to their size. Millions of installations in communications, aerospace, electronic, telephone, radio and TV applications.

Certificates and Declarations (Document Number)		
Data Sheet, Technical Information	GSC175	
Instructions and Manuals	GSC175	
RoHS Information	9AKK107992A4006	

Classifications		
ETIM 6	EC002650 - Connection for screened wires	
ETIM 7	EC002650 - Connection for screened wires	
UNSPSC	39121432	
WEEE Category	Product Not in WEEE Scope	
IDEA Granular Category Code (IGCC)	4603 >> Electrical terminals	

Categories

 $Low\ Voltage\ Products\ \rightarrow\ Mire\ Management\ and\ Connectivity\ \rightarrow\ Compression\ \&\ Mechanical\ Connectors$

GSC175 3

