

CII

TE Internal #: 1617048-9

General Purpose Power Relay, DC, Non-Polarized, Monostable, 6 Form C 6PDT-CO, .00003 A Contact Rating, 26.5 VDC Coil Voltage,

3.511 W Coil Power

View on TE.com >



Relays & Contactors > Electromechanical Relays



Relay & Contactor Type: General Purpose Power Relay

Current Type: DC

Coil Magnetic System: Non-Polarized, Monostable

Contact Arrangement: 6 Form C 6PDT-CO

Main Termination & Connection Type

Coil Termination & Connection Type

Product Mounting Feature Type

Mechanical Attachment

Product Mount Type

Contact Current Rating: .00003 A

Features

Product Type Features

Product Type Features	
Relay & Contactor Type	General Purpose Power Relay
Configuration Features	
Contact Arrangement	6 Form C 6PDT-CO
Electrical Characteristics	
Coil Resistance	200 Ω
Contact Switching Voltage (Max)	.03 VDC
Contact Current Rating	.00003 A
Coil Voltage Rating	26.5 VDC
Coil Power Rating DC	3.511 W
Body Features	
Enclosure Type	Hermetically Sealed
Termination Features	

Solder Hook Terminals

Solder Hook Terminals

Panel Mount

Flange with Mounting Holes



Usage Conditions

Operating Temperature Range	-65 – 125 °C
Environmental Ambient Temperature (Max)	125 °C[257 °F]
Operation/Application	
Vibration Resistance	20G's, 10 – 2000Hz

Shock Resistance

Current Type

ZOG's, 10 – Z000Hz

100G's, 6ms

DC

Coil Magnetic System Non-Polarized, Monostable

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not lead free process capable

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts







Customers Also Bought



TE Part #650139-000 D-436-52



TE Part #5950152008 TFE-2-X-STK



TE Part #788159-2 SLD CPC RCPT ASSY,13-9,STD SEX





TE Part #1616060-1 A931F=CONTACTOR, SPST-NC, 600A











TE Part #6500760004 D-436-38CS454

TE Part #3-1617748-7 FCA-125-34

Documents

Product Drawings

RD6CAH2600 = M5757/1-021

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1617048-9_A.2d_dxf.zip

General Purpose Power Relay, DC, Non-Polarized, Monostable, 6 Form C 6PDT-CO, . 00003 A Contact Rating, 26.5 VDC Coil Voltage, 3.511 W Coil Power



English

Customer View Model

ENG_CVM_CVM_1617048-9_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1617048-9_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

RELAY

English