



### Main

Product or component type	Wireless indication auxiliary
Device short name	OF[RETURN]SD[RETURN]SDE
Device application	Breaker status monitoring
Range compatibility	ComPacT new generation ComPacT NSX new generation ComPacT new generation ComPacT NSX DC new generation ComPacT new generation ComPacT NS new generation
Local signalling	ON/OFF indication for open/close Trip indicator for relay trip indicator Fault trip for electrical fault
Fault type	General electric fault
Connectivity to devices	ZigBee device
Communication network type	ZigBee IEEE 802.15.4 (2405...2480 MHz)

### Complementary

Mounting mode	Clip-on
Body material	Plastic
Status LED	With
Power supply type	Battery
Battery life	10 year(s)
[Uimp] rated impulse withstand voltage	8 kV
Mechanical durability	50000 cycles
Standards	EN/IEC 60947 UL 489

### Environment

IP degree of protection	IP4X conforming to IEC 60529
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-25...85 °C
Relative humidity	95 % at 55 °C

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>