

Product datasheet

uvex 1 x-cite 8642 1-3

Safety boot DIN EN ISO 20345:2022+A1:2024 S3L FO SR

Sizes: 34 - 44 | Width: 10, 11, 12



AREA OF APPLICATION

The light application covers all areas in which work is carried out indoors in particular and which do not place high demands on the physical properties of the outsole of a safety shoe.

OUTSOLE

Polyurethane outsole



- PU outsole
- antistatic
- short-term heat-resistant up to 120°C
- excellent slip resistance (**SR**)
- oil- and fuel resistant (**FO**)
- free of silicones, plasticisers and other substances that interfere with wetting agents



FEATURES	
Upper material	<ul style="list-style-type: none"> • hydrophobic leather • water-repellent (WPA)
Lining material	<ul style="list-style-type: none"> • breathable textile (clima zone)
Fastening	<ul style="list-style-type: none"> • laces and zip
Comfort	<ul style="list-style-type: none"> • soft padding on collar
Innersole	<ul style="list-style-type: none"> • removable comfortable innersole
Furthermore	<ul style="list-style-type: none"> • metal-free
PROTECTIVE FEATURES	
Toe cap	<ul style="list-style-type: none"> • metal-free toe cap with carbon
Penetration resistance	<ul style="list-style-type: none"> • metal-free, textile penetration resistance
CERTIFICATES	
uvex medicare	<ul style="list-style-type: none"> • certified for orthopaedic innersoles according to the description in DGUV 112-191
ESD	<ul style="list-style-type: none"> • protection against electrostatic charge according to EN 61340-4-3 und EN 61340-5-1
SUSTAINABILITY	
CO2 footprint	<ul style="list-style-type: none"> • 17.79 kg Cradle-to-Customer • 19.59 kg Cradle-to-Grave (calculation date 03/2026)
Recycled/sustainable materials	<ul style="list-style-type: none"> • penetration resistance and removable innersole made wholly or partly from recycled materials • free from harmful substances in accordance with the uvex restricted substances list
ACCESSORIES/ SPARE PARTS	
Replacement innersole	<ul style="list-style-type: none"> • 8639 7-9