



## TECHNICAL DATA

# Foodlube Hi-Torque Mineral Hydrocarbon Free, Synthetic Gearbox Fluids

Viscosity Grades ISO VG 150 and 320

### Description

ROCOL Foodlube Hi-Torque is a range of non toxic, mineral hydrocarbon free gearbox fluids for use within clean environments.

ROCOL Foodlube Hi-Torque Fluids are mineral hydrocarbon free, made using only FDA listed ingredients and authorised by the USDA for H1 use.

ROCOL Foodlube Hi-Torque Fluids increase service intervals, operate over a wide temperature range and provide excellent corrosion protection.

ROCOL Foodlube Hi-Torque Fluids are resistant to water wash off and are particularly suitable for use in wet conditions and applications where frequent wash downs occur.

### Outstanding Features

- Good load carrying capabilities FZG load stage 12
- Tenacious, non drip film
- Excellent corrosion protection
- Good water displacing properties

### Directions for use

Gearboxes should be drained and flushed prior to filling, to the normal top up level, with ROCOL Foodlube Hi-Torque

### Technical Data

*Appearance* : Yellow, almost colourless

*Base fluid* : Polyalkylene Glycol

*Viscosities (40°C)* : 150 and 320 cSt

*Operating temperature range* : -20°C to +150°C

*Storage* : Store at normal ambient  
temperature, 0°C to 40°C

*continued.....*

#### ROCOL Limited

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: 0113 232 2600 Fax: 0113 232 2760

ROCOL is a BS EN ISO 9002 registered company.

ROCOL is a trade mark of ROCOL Limited.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.



## Health and Safety

Further Technical Data and Health and Safety information (COSHH, MSDS) is available from the Customer Service Department, ROCOL Ltd., ROCOL House, Swillington, Leeds, LS26 8BS, England.

Telephone: 0113 232 2700, (When calling from outside UK: 44 113 232 2700).

Fax: 0113 232 2760, (When faxing from outside UK: 44 113 232 2760).

Issue:1551a 27/08/97

### **ROCOL Limited**

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: 0113 232 2600 Fax: 0113 232 2760

ROCOL is a BS EN ISO 9002 registered company.

ROCOL is a trade mark of ROCOL Limited.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.