

TECHNICAL DATA SHEET

Update of the document: 11/02/16
ISO reference of this document : DON/LS 03.4208.A



LEMAITRE SECURITE SAS
17 rue Bitschhoffen
CS 90024
F 67350 La Walck FRANCE
Tél. : +33 (0)3 88 72 28 80
Fax : +33 (0)3 88 07 05 37
www.lemaitre-securite.com
contact@lemaitre-securite.com



CARIBU S2 CI SRC
High shoe in white water-repellent microfiber

PROTECTIONS FOR THIS MODEL



Sizes available from 35 (2) to 48 (13)
Weight of one pair in size 37 (4) : about 890 gr.
Norm EN ISO 20345 : 2011
AET N° : 0160 1441 08

Upper features

- Upper : water-repellent white microfiber
- Lining : three-dimensional micro-porous textile
- Back part : synderm
- Tongue marking : size, manufacturer, manufacture date (month, year), norm, protection, CE marking.

Protections

- From 35 (2) to 36(3) : toecap in steel (200 joules)
- From 37 (4) to 48(13) : Toecap : polycarbonate (200 joules)

Fitting features

- Natur'form (large)
- Lasting insole : textile
- Insock : foam and textile

Sole features

- Material : dual density polyurethane
- Comfort sole density : 0,45
- Comfort sole color : white
- Outsole density : 1.10
- Outsole color : blue
- Slip resistance SRA (flat) : 0,36 ; (heel) : 0,34
- Slip resistance SRB (flat) : 0,19 ; (heel) : 0,18

Requirements of the norm EN ISO 20345

Steel toecap Polycarbonate toecap Aluminum toecap (200 joules)

Steel midsole Non metallic midsole

A A Electric resistance – Antistatic shoes.

CI CI Insulating sole against cold.

E E Heel energy absorption.

Fo FO Hydrocarbons resistance of the undermine sole.

Hi HI Insulating sole against heat.

Hro HRO Heat resistance of the sole.

M M Metatarsal protection.

P P Perforation resistance.

Wru WRU Water repellent upper.

Wr WR Water repellent junction upper/sole.



Regarding the norm EN ISO 20345, the minimum results for slip resistance to get the SRC certificate are :

SRA (flat) $\geq 0,32$

SRA (heel) $\geq 0,28$

SRB (flat) $\geq 0,18$

SRB (heel) $\geq 0,13$

Advantages = End users benefits

High safety shoe special agri-food

- ➔ **Shoe washable and sterilizable**
- ➔ Upper in **microfiber water repellent and breathable**
- ➔ Light and soft shoe
- ➔ **Three tridimensional textile lining** : Breathable thanks to its alveolated structure which is soft and allows better ventilation sweating for improved comfort
- ➔ **Antibacterial insock**

Outsole :

- ✓ **Slip resistant sole** with a studded open structure for better drainage of liquids
- ✓ **Open heel** for the ladders
- ✓ **Shock absorption heel**
- ✓ **Sole with a dynamic spring** effect of the sole that returns energy when the foot lifts off the ground
- ✓ **Injected polyurethane dual density**
- ✓ **Insulating against the cold**