




---

 PRODUCT-DETAILS

## S201M-C4DC

### Miniature Circuit Breaker - S200MDC - 1P - 4 A - C - (230 V) 10 kA




---

**General Information**

Extended Product Type	S201M-C4DC
Product ID	2TAZ112100R0044
Catalog Description	Miniature Circuit Breaker - S200MDC - 1P - 4 A - C - (230 V) 10 kA
Long Description	Miniature Circuit Breaker - S200MDC - 1P - C - 4 A

---

**ABB EcoSolutions**

ABB EcoSolutions	Yes
EcoSolutions Profile	9AKK108471A1001
Recyclability Rate of the Product acc. to EN45555	Design for Closing Resource Loops - Standard EN45555 - 91.45 %
ABB Site Meeting Group Waste To Landfill Target	No non-hazardous waste is sent to a landfill UL 2799 Zero Waste To Landfill Validation available
Sustainable Material Content in Packaging (wt. %)	Recycled Cardboard - 100 %
Extended Product Lifetime	Product Durability
End Of Life	9AKK108469A7114

Disassembling  
Instructions

Environmental Product Declaration - EPD	9AKK108468A8287
---	-----------------

**Technical**

Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ )	(220 V DC) 10 kA
Energy Limiting Class	3
Number of Protected Poles	1
Number of Poles	1P
Release Type	C
Options Provided	DC application
Accessories Available	Yes
Connecting Capacity	Flexible 0 ... 25 mm <sup>2</sup> Rigid 0 ... 35 mm <sup>2</sup>

**Electrical**

Tripping Characteristic	C
Rated Voltage ( $U_r$ )	220 V
Rated Operational Voltage	220 V DC
Rated Insulation Voltage ( $U_i$ )	440 V
Rated Impulse Withstand Voltage ( $U_{imp}$ )	4 kV
Input Voltage Type	DC
Rated Current ( $I_n$ )	4 A
Rated Short-Circuit Capacity	(230 V) 10 kA
Rated Conditional Short-Circuit Current ( $I_{nc}$ )	(230 V) 10 kA
Power Loss	Total 1.48 W
Overvoltage Category	III

**Material Compliance**

RoHS Information	No declaration needed
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business

**Environmental**

Ambient Air Temperature	Operation -25 ... +55 °C
Degree of Protection	IP20
Pollution Degree	3

---

**Dimensions**

Width in Number of Modular Spacings	1
Product Net Width	0.018 m
Product Net Height	0.088 m
Product Net Depth / Length	0.044 m
Product Net Weight	0.125 kg
Built-In Depth (t <sub>2</sub> )	69 mm

---

**Engineering**

EPLAN Data	9AAC187310_EPLAN
------------	------------------

---

**Ordering**

Package Level 1 Units	carton 12 piece
Package Level 1 Gross Weight	1.375 kg

---

**Certificates and Declarations**

Declaration of Conformity - CE	No declaration needed
--------------------------------	-----------------------

---

**Installation**

Instructions and Manuals	No document needed
--------------------------	--------------------

---

**Popular Downloads**

Data Sheet, Technical Information	No document needed
-----------------------------------	--------------------

---

**External Classifications and Standards**

ETIM 9	EC000042 - Miniature circuit breaker (MCB)
ETIM 10	EC000042 - Miniature circuit breaker (MCB)
eClass	V11.0 : 27141901
Object Classification Code	F
Standards	IEC/EN 60898-2 GB 10963 IEC/EN 60947-2 GB 14048

---

## Categories

---

Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs → Miniature Circuit Breakers MCBs → S200MDC

