

1419570

https://www.phoenixcontact.com/in/products/1419570

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Housing screw connection, Socket, M12, Rear mounting

Your advantages

- Tolerance-compensating function between PCB and housing
- · Prevents force being applied to soldering spots
- · Easy integration thanks to tool-free mounting
- · Optional port sealing without protective cap

Commercial data

Item number	1419570
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	ABQ
Product key	ABQBDG
GTIN	4055626207056
Weight per piece (including packing)	8.77 g
Weight per piece (excluding packing)	8.77 g
Customs tariff number	79070000
Country of origin	DE



1419570

https://www.phoenixcontact.com/in/products/1419570

Technical data

Notes

The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must
also be taken into consideration.

Product properties

Product type	Panel mounting base
Thread type	M12

Material specifications

Material	Die-cast zinc, nickel-plated (Threaded sleeve)
Flammability rating according to UL 94	V0
Seal material	FKM

Connector

Connection 1

Head design	Socket
Head thread type	M12

Environmental and real-life conditions

Ambient conditions

Degree of protection (when plugged in)	IP67 (correctly plugged in and locked)
Degree of protection	IP67 (correctly plugged in and locked)
	IP67
Ambient temperature (operation)	-25 °C 85 °C (Plug / socket)
	-40 °C 85 °C (without mechanical actuation)
UL Type Rating	Type 4 (indoor use only)

Standards and regulations

M12

Standard designation	M12 connector
Standards/specifications	IEC 61076-2-101

Mounting

Mounting type	Rear mounting 2-section, lockable
Assembly note	2-section, lockable



1419570

https://www.phoenixcontact.com/in/products/1419570

Classifications

ECLASS

	ECLASS-11.0	27440224
	ECLASS-13.0	27440224
ETIM		
	ETIM 9.0	EC003556
UNSPSC		
	UNSPSC 21.0	31171600



1419570

https://www.phoenixcontact.com/in/products/1419570

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	d511ff79-1491-495e-ba45-64aacef202a2



1419570

https://www.phoenixcontact.com/in/products/1419570

Accessories

SACC-BP-F-FIX/NUT-BK-SMD - Fixing sleeve

1419568

https://www.phoenixcontact.com/in/products/1419568



Fixing sleeve for M12 housing screw connection with tolerance-compensating function, for SMD-solderable M12 socket contact inserts.

SACC-BP-F-FIX/NUT-CY-SMD - Fixing sleeve

1419565

https://www.phoenixcontact.com/in/products/1419565



Fixing sleeve for M12 housing screw connection with tolerance-compensating function, for SMD-solderable M12 socket contact inserts.



1419570

https://www.phoenixcontact.com/in/products/1419570

SACC-BP-F-FIX/NUT-GN-SMD - Fixing sleeve

1419566

https://www.phoenixcontact.com/in/products/1419566



Fixing sleeve for M12 housing screw connection with tolerance-compensating function, for SMD-solderable M12 socket contact inserts.

SACC-BP-F-FIX/NUT-VT-SMD - Fixing sleeve

1419567

https://www.phoenixcontact.com/in/products/1419567



Fixing sleeve for M12 housing screw connection with tolerance-compensating function, for SMD-solderable M12 socket contact inserts.

Phoenix Contact 2025 @ - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT (I) Pvt. Ltd. A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420 info@phoenixcontact.co.in