



TECHNICAL DATA

FOODLUBE MULTI-PURPOSE BEARING GREASE

High performance multi-purpose
food grade bearing grease

Description

ROCOL FOODLUBE MULTI-PURPOSE BEARING GREASE is a white, tenacious non-toxic (USDA H1), bearing grease designed for the effective lubrication and protection of all types of ball, roller and plain bearings operating in the food and other clean industries.

Outstanding Features

- Excellent load carrying capabilities
- FDA listed ingredients and USDA H1 authorised
- Highly resistant to water washout
- Excellent corrosion protection
- Does not contain any animal derived materials

Directions for use

ROCOL FOODLUBE MULTI-PURPOSE BEARING GREASE can be applied manually via the new unique HANDI applicator.

Alternatively ROCOL FOODLUBE MULTI-PURPOSE BEARING GREASE may be applied automatically via the new ROCOL FOODLUBE AUTOLUBE. The ROCOL FOODLUBE AUTOLUBE is an electromechanical unit which is made of two parts:- a grease cartridge which is replaceable and a reusable drive unit. To install the unit simply follow the steps below:-

- Ensure the switch is in the OFF position.
- Unscrew the lid.
- On the drive unit you will see a circuit board with a dip switch simply set this to the required dispense period as illustrated on the product label.
- Replace the lid over the drive unit.
- Screw the lid manually. Take care that the lid fits closely with the grease cartridge.
- Take the cap off the grease cartridge unit.
- Turn the switch to the ON position with a coin.
- Screw the ROCOL FOODLUBE AUTOLUBE into the lubrication point.

ROCOL Limited

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: 0113 232 2600 Fax:: 0113 232 2760

ROCOL is a BS EN ISO 9002 registered company.

ROCOL is a trade mark of ROCOL Limited

The information in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which effect the use and performance of our products for which reason the information in this publication is given without

responsibility



For more detailed instructions please refer to the installation instructions supplied with your ROCOL FOODLUBE AUTOLUBE.

ROCOL FOODLUBE MULTI-PURPOSE BEARING GREASE is compatible with other soap thickened greases. However, for best results, bearings should be cleaned or purged of the previous lubricant.

Technical Data

<i>Appearance</i>	: <i>White, tenacious grease</i>
<i>NLGI No. (IP 50) (ASTM D217)</i>	: <i>NLGI No. 2</i>
<i>Base fluid type</i>	: <i>Polyalkylene Glycol</i>
<i>Thickener</i>	: <i>Calcium Soap</i>
<i>Temperature range (ASTM D128)</i>	: <i>-20°C to +110°C</i>
<i>Shell 4 Ball (IP239) (ASTM D2596)</i>	
<i>Weld Load</i>	: <i>280kg</i>
<i>Load Wear Index</i>	: <i>55</i>
<i>Copper Corrosion test (IP112) (ASTM D130)</i>	: <i>Pass</i>
<i>Corrosion test (EMCOR) (IP 220)</i>	: <i>0:0</i>
<i>Water Washout Test (IP215)(ASTM D1264)</i>	: <i><1%</i>
<i>Storage</i>	: <i>Store in a cool/dry place</i>
<i>Pack Sizes</i>	: <i>HANDI 150ml</i>
	: <i>AUTOLUBE cartridge 120ml</i>

Health and Safety

Further Technical Data and Health and Safety information (COSHH, MSDS) is available from the Customer Service Department, ROCOL Ltd., ROCOL House, Swillington, Leeds, LS26 8BS, England.

Telephone: 0113 232 2700, (When calling from outside UK: 44 113 232 2700).

Fax: 0113 232 2760, (When faxing from outside UK: 44 113 232 2760).

Issue: 1522HAa 27/10/98

ROCOL Limited

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: 0113 232 2600 Fax: 0113 232 2760

ROCOL is a BS EN ISO 9002 registered company.

ROCOL is a trade mark of ROCOL Limited

The information in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which effect the use and performance of our products for which reason the information in this publication is given without responsibility

