



Underwriters Laboratories Inc.®

File E36479
Project 79ME2711

Issued: June 12, 1979
*Revised: December 10, 1991

REPORT

on

COMPONENT - SWITCHES, SPECIAL USE

**Burgess Micro Switch Co., Ltd.
Dukes Way, Team Valley
Gateshead 11, England**

Copyright © 1979 Underwriters Laboratories Inc.

Underwriters Laboratories Inc. authorizes the above-named company to reproduce this Report provided it is reproduced in its entirety.

Underwriters Laboratories Inc. authorizes the above-named company to reproduce that portion of this Report consisting of this Cover Page through Page 1C.

D E S C R I P T I O NPRODUCT COVERED:

Special-Use Switches, Component

<u>Cat. No.</u>	<u>Electrical Rating</u>	<u>Temp(°C)</u>	<u>POL/THR</u>	<u>PP</u>	<u>ENDUR</u>	<u>SPCOA</u>
KB5-A2 w/wo suff K, KR before -A2 w/wo suff T ap/UL KB5EQ w/wo suff R, R2 ap/UL KB5F w/wo suff K, KR, T ap/UL	20 A, 250 V ac 1 hp, 125 V ac 2 hp, 250 V ac	65	1/1	-	6 K	-
KB5-A2 w/wo suff K, KR before -A2 w/wo suff T ap/ULS KB5EQ w/wo suff R, R2 ap/ULS KB5F w/wo suff K, KR, T ap/ULS	20 A, 250 V ac 1 hp, 125 V ac 2 hp, 250 V ac	65	1/1	-	100 K	-

ap - w/wo Y1
Y2, Y3, YC, YR1,
GP

CAT NO: f/b = followed by w/wo = with or without

ELECTRICAL RATING: "R" = Resistive "L" = AC Tungsten "T" = AC and DC Tungsten
POL/THR: No. of Poles/No. of Throws. "M" indicates "Multi"
(e.g. 2/M indicates 2 pole, Multi-throw)

PP: Per Pole, "PP" in this column indicates each pole may carry the rated current
(for 2 or more pole switches), with opposite polarity between adjacent poles.

ENDUR: Endurance rating

SPCOA: Applicable Special Conditions of Acceptability are indicated here in numeric form. Refer to the following pages for corresponding Special Conditions of Acceptability.