



POLICLEAN PCLD non-woven cleaning fabric dia. 125x13 mm hole dia. 22.3 mm for coarse cleaning work

**POLICLEAN PCLD non-woven cleaning fabric dia. 125x13
mm hole dia. 22.3 mm for coarse cleaning work**

Item number: [44692725](#)

EAN: [4007220515297](#)

The non-woven cleaning material is glued onto a glass-fabric base. This makes POLICLEAN discs suitable for use in face-down grinding. For coarse cleaning work, e.g. removing paint, scale, heat discolouration, rust and adhesive residue.

POLICLEAN is a coarsely structured, abrasive, non-woven cleaning fabric that was developed from a special combination of synthetic fibres and abrasive grain.

Technical information

Abrasive	Silicon carbide SiC/C
Dia. external	125 mm
Dia. hole	22.23 mm
Max. RPM	10000 RPM
PFERD TOOLS type	PCLD
RPM, optimum	5.000 - 7.000 RPM
Version	PCLD
Width	13 mm

Advantages

- ✓ High flexibility and open structure mean optimal adjustment to contours and no clogging of the tool itself.
- ✓ The standard version (black) generates finer surfaces and is more flexible.

Recommendations for use

- ✓ For the best results, use at a recommended cutting speed of 30-35 m/s.
 - ✓ Preferably for use on slow-running angle grinders.
-

Safety notes

- ✓ For safety reasons, the maximum permitted rotational speed indicated must never be exceeded.
-

Materials that can be worked

- ✓ Aluminium
- ✓ Annealed cast iron
- ✓ Brass
- ✓ Bronze
- ✓ Cast steel
- ✓ Cobalt-based alloys
- ✓ Copper
- ✓ Elastomers
- ✓ Fibre-reinforced thermosetting plastics (GRP, CRP)
- ✓ Grey/nodular cast iron (GG/GJL, GGG/GJS)
- ✓ Hardened, heat-treated steels over 1.200 N/mm² (< 38 HRC)
- ✓ Nickel-based alloys (e.g. Inconell and Hastelloy)
- ✓ Stainless steel (INOX)
- ✓ Steel materials with a hardness > 54 HRC
- ✓ Steels up to 1,200 N/mm² (< 38 HRC)
- ✓ Thermoplastics
- ✓ Titanium
- ✓ Titanium alloys
- ✓ Zinc

Applications

- ✓ Cleaning
 - ✓ Roughening
 - ✓ Surface work
-

Drive types

- ✓ Drive spindle
 - ✓ Flexible shaft drive
 - ✓ Straight grinder
-

**PFERD
TOOLS**



August Rüggeberg GmbH & Co. KG
Hauptstraße 13
51709 Marienheide

+49 2264 9-0

+49 2264 9-400

info@pferd.com