

## Features

- RS PRO and Little Giant dual-branded professional solution
- Independent side-mounted stabiliser bars for uneven ground applications
- Heavy-wall military-grade aluminium construction
- Rapid Lock® adjustment system for fast height changes
- Palm Button hinge system for easy configuration changes
- Tip & Glide® wheels for easy transportation
- Multi-position ladder design for maximum versatility
- Suitable for professional and intensive use
- Can be levelled on uneven surfaces without compromising stability
- Compatible with ladder trestle accessories

## RS PRO by Little Giant®

### Conquest™ All-Terrain Multi-Purpose Ladder



RS PRO® is the own brand of RS. Combining quality, choice and value, RS PRO products are professionally approved and trusted by engineers worldwide. Little Giant® is a registered trademark of Little Giant Ladder Systems.

## Product Description

The RS PRO by Little Giant® Conquest™ All-Terrain Multi-Purpose Ladder is a professional-grade access solution designed for demanding applications where stability, versatility and durability are essential. Combining the trusted quality of RS PRO with Little Giant's innovative ladder technology, the Conquest™ enables safe and efficient working across uneven terrain and challenging job sites.

Featuring independent side-mounted stabiliser bars, Rapid Lock® adjustment technology and heavy-wall military-grade aluminium construction, the Conquest™ provides exceptional flexibility for a wide variety of industrial, maintenance and construction tasks.

The ladder can be configured in multiple positions including:

- A-Frame Ladder
- Extension Ladder
- Staircase Ladder
- 90° Wall Ladder
- Trestle & Plank Scaffolding (with compatible accessories)

## Standards and Compliance

|                              |                              |
|------------------------------|------------------------------|
| <b>Standard</b>              | EN131-4:2020 Professional    |
| <b>Maximum Load Capacity</b> | 150kg                        |
| <b>Usage Classification</b>  | Professional / Intensive Use |
| <b>Material</b>              | Aluminium                    |

## Applications

|                                    |
|------------------------------------|
| Roofing and external building work |
| Painting and decorating            |
| Facilities maintenance             |
| Construction projects              |
| Utilities and infrastructure work  |
| Ground maintenance operations      |
| Industrial maintenance             |
| Property maintenance and repair    |

## Technical Specification

|                        |                                          |
|------------------------|------------------------------------------|
| Brand                  | RS PRO by Little Giant®                  |
| Product Type           | Multi-Purpose Ladder                     |
| Material               | Aluminium                                |
| Ladder Configuration   | Multi-Position                           |
| Maximum Working Load   | 150kg                                    |
| Rung Depth             | 25mm                                     |
| Distance Between Rungs | 297mm                                    |
| Wheels                 | Integrated Tip & Glide® Wheels           |
| Levelling System       | Independent Side-Mounted Stabiliser Bars |
| Colour                 | Aluminium/Silver                         |

## Product Dimensions

| Stock No. | Rungs / Sections | Last Climbing Height (mm) | Approx. Working Height (mm) | Extended Length (mm) | Closed Length (mm) | Weight (kg) |
|-----------|------------------|---------------------------|-----------------------------|----------------------|--------------------|-------------|
| 889696    | 4 x 4            | 3530                      | 5480                        | 2720 - 4550          | 1400               | 16.2        |
| 889697    | 5 x 4            | 4720                      | 6670                        | 3330 - 5770          | 1700               | 19.5        |
| 889698    | 6 x 4            | 5890                      | 7840                        | 3940 - 6690          | 2010               | 24.5        |

## A-Frame Working Heights

| Stock No. | Width (mm) | Depth (mm) |
|-----------|------------|------------|
| 889696    | 610        | 230        |
| 889697    | 690        | 230        |
| 889698    | 760        | 230        |

## Shipping Information

| Stock No. | Shipping Length (mm) | Shipping Width (mm) | Shipping Depth (mm) | Gross Weight (kg) |
|-----------|----------------------|---------------------|---------------------|-------------------|
| 889696    | 1430                 | 635                 | 220                 | 18.6              |
| 889697    | 1730                 | 710                 | 220                 | 22.5              |
| 889698    | 2030                 | 785                 | 220                 | 28.4              |



## Key Features Explained

### All-Terrain Levelling System

Independent side-mounted stabiliser bars allow the ladder to be levelled on uneven surfaces, helping users work safely on sloped ground or challenging job sites. The stabilisers can be adjusted independently to compensate for differences in ground height.

### Rapid Lock® Adjustment

The Rapid Lock® system enables quick and secure ladder height adjustment. Users simply twist the locks, extend the ladder to the desired height and relock for secure positioning.

### Palm Button Conversion System

Palm Buttons allow rapid transition between storage, A-frame and extension ladder configurations, improving productivity on site.

### Tip & Glide® Wheels

Integrated wheels make transporting the ladder between work locations easier while reducing operator effort.

## Safety Note

Always inspect ladder equipment before use and follow all applicable workplace safety procedures. Ensure the ladder is fully locked into position before climbing.