



Hyspin AWH-M

High viscosity index anti-wear hydraulic oils

Description

The Castrol Hyspin™ AWH-M hydraulic oil range of shear stable high viscosity index lubricants are based on the latest stabilised zinc additive technology.

Application

Hyspin AWH-M contains a shear stable additive system which helps maintain the viscosity characteristics of the product over a wide temperature range even during prolonged use and imparts a very low pour point which enables the product to be used in very cold environments. It exhibits excellent corrosion and wear protection as well as outstanding thermal and oxidative stability. In addition, Hyspin AWH-M has excellent hydrolytic stability and separates rapidly from water contamination upon standing. Applications include:

- Outdoor equipment which are likely to operate in wide temperature ranges, such as machinery subjected to cold start up conditions and high temperature continuous running. Examples include off-highway and marine applications.
- Indoor manufacturing equipment that incorporates control systems requiring minimal viscosity change with temperature. Examples include precision machine tools.
- The Hyspin AWH-M range is fully compatible with elastomer materials commonly used for static and dynamic seals, such as nitrile, silicone and fluorinated (e.g. Viton) polymers.

Hyspin AWH-M is classified as follows:

DIN 51502 classification – HVLP

ISO 6743/4 - Hydraulic Oils Type HV

Hyspin AWH-M grades meet the requirements (for appropriate viscosity grade) of:

DIN 51524 Part 3

Cincinnati Lamb (Milacron) P 68-69-70

Denison (Parker Hannafin) HF-0

US Steel 126 & 127

Eaton (formerly Vickers) I-286-S & M-2950-S Bosch Rexroth RE07075/RE90220

Advantages

- High viscosity index and low pour point enables the product to be used over a wide temperature range, with good shear stability which means no excessive loss in viscosity due to mechanical shearing.
- Excellent anti-wear performance provides extended wear protection for hydraulic pumps. Reduced down time due to unscheduled maintenance and savings from replacement part costs.
- Excellent water separation and hydrolytic stability means reduced down time through prolonged lubricant life and increased equipment reliability.
- Good filterability gives a cleaner system with less frequent filter changes.

Typical Physical Characteristics

Test	Method	Units	AWH-M 15	AWH-M 32	AWH-M 46	AWH-M 68	AWH-M 100	AWH-M 150
ISO Viscosity Grade	-	-	15	32	46	68	100	150
Density @ 15°C	ISO 12815/ASTM D4052	g/ml	0.88	0.88	0.88	0.88	0.89	0.89
K.V @ 40°C	ISO 3104/ASTM D445	mm ² /s	15	32	46	68	100	150
K.V @ 100°C	ISO 3104/ASTM D445	mm ² /s	3.83	6.3	8.1	10.4	13.45	17.7
Viscosity Index	ISO 2909/ASTM 2270	-	>150	>150	>150	>140	>150	>130
Pour Point	ISO 3016/ASTM D97	°C	-48	-39	-36	-36	-33	-30
Flash Point, PMCC	ISO 2719/ASTM D93	°C	>150	>190	>190	>190	>190	>190
Foam Seq 1	ISO 6247/ASTM D892	mls	20/0	20/0	20/0	20/0	20/0	20/0
Water Separability @ 54°C	ISO 6614/ASTM D1401	Mins	5	10	15	15	-	-
Water Separability @ 82°C	ISO 6614/ASTM D1401	Mins	-	-	-	-	20	20
Air Release Value	ISO 9120/ASTM D3427	Mins	4	4	8	8	12	24
FZG fail stage (A8.3/90)	ISO 14635-1/ DIN 51354	-	-	11	12	12	12	12
Rust Test (24 hrs Distilled water)	ISO 7210/ASTM D665A	-	Pass	Pass	Pass	Pass	Pass	Pass
Rust Test (24 hrs Synthetic sea water)	ISO 7210/ASTM D665B	-	Pass	Pass	Pass	Pass	Pass	Pass
K.V. @ 100°C after 4 hours KRL	DIN 51350 T6	% loss	-	-	9.5	-	-	-

Subject to usual manufacturing tolerances.

Hyspin AWH-M

18 Mar 2014

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol Australia, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Australia Pty Limited - ABN 87 008 459 407 – 717 Bourke Street, Docklands Vic 3008

Technical Advice Line: 1300 557 998 Customer Service: 1300 722 088

www.castrol.com/industrial www.msds.castrol.com.au