


Spezifikation für Freigabe / specification for release

Kunde / customer : _____
 Artikelnummer / part number : **74272592**
 Bezeichnung : **BLOCKKERN GETEILT (konfektioniert)**
 description : **SPLIT FLAT FERRITE (assembled)**



DATUM / DATE : 2006-09-29

A Mechanische Abmessungen / dimensions:




A	63,0 +0,0/-1,2	mm
B	2,0 ± 0,8	mm
C	13,0 +0,0/-1,0	mm
D	15,0 ± 0,5	mm
E	52,0 +1,0/-0,2	mm

B Elektrische Eigenschaften / electrical properties:

Eigenschaften / properties	Testbedingungen / test conditions		Wert / value	Einheit / unit	Tol.
Impedanz @ 1 Wg./ impedance @ 1 turn	25 MHz	Z	44	Ω	± 25%
Impedanz @ 1 Wg./ impedance @ 1 turn	100 MHz	Z	101	Ω	± 25%
Impedanz @ 2 Wg./ impedance @ 2 turn		Z		Ω	
Impedanz @ 2 Wg./ impedance @ 2 turn		Z		Ω	

C



D Prüfgeräte / test equipment:

HP 4191 B für/for Z und/and material
16092A - Klemme / clamp
AWG26 - Ø 0,5mm - Länge/length: 165 mm

E Testbedingungen / test conditions:

Luftfeuchtigkeit / humidity: 33%
 Umgebungstemperatur / temperature: + 20°C

F Werkstoffe & Zulassungen / material & approvals:

Basismaterial / base material: 4 W 620

G Eigenschaften / general specifications:

Curietemperatur / curie temperature: +150°C
 für Flachbandkabel / for flat cable [max]: 40 pol.
 Lagertemperatur / storage temperature: -55°C ~ + 125°C
 Betriebstemp. / operating temperature: -25°C ~ +125°C

Freigabe erteilt / general release:	Kunde / customer		
.....		SMU	Update 06-09-29
Datum / date	Unterschrift / signature	SSt	Update Tape 05-11-16
	Würth Elektronik	SST	Update tolerances 05-06-27
		LF	RoHS update 04-10-11
.....		JH	Neugestaltung 00-12-06
Geprüft / checked	Kontrolliert / approved	Name	Änderung / modification Datum / date

Würth Elektronik eiSos GmbH & Co. KG

D-74638 Waldenburg · Max-Eyth-Strasse 1 - 3 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400
<http://www.we-online.com>


Spezifikation für Freigabe / specification for release

Kunde / customer : _____
 Artikelnummer / part number : **74272592**
 Bezeichnung : **BLOCKKERN GETEILT (konfektioniert)**
 description : **SPLIT FLAT FERRITE (assembled)**



DATUM / DATE : 2006-09-29

H Impedanzverlauf / impedance curve:



B: 1 x durch Bohrung Ferrit / 1 x times trough ferrite

Freigabe erteilt / general release:	Kunde / customer			
.....	SMU	Update	06-09-29
Datum / date	Unterschrift / signature	SSt	Update Tape	05-11-16
	Würth Elektronik	SST	Update tolerances	05-06-27
.....	LF	RoHS update	04-10-11
Geprüft / checked	Kontrolliert / approved	JH	Neugestaltung	00-12-06
		Name	Änderung / modification	Datum / date

This electronic component has been designed and developed for usage in general electronic equipment. Before incorporating this component into any equipment where higher safety and reliability is especially required or if there is the possibility of direct damage or injury to human body, for example in the range of aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc, Würth Elektronik eiSos GmbH must be informed before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.

Würth Elektronik eiSos GmbH & Co. KG

D-74638 Waldenburg · Max-Eyth-Strasse 1 - 3 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400
<http://www.we-online.com>