

Parker Product Datasheet



Parker Ball Bearing Rotary Fittings are used to connect a fixed point to a rotating, swinging or moving part via hoses. These products are used to prevent torsion and small hose radius.

PART NUMBER: DG101/08SHDCF

SHAPE: Straight

ACCESSORIES INCLUDED: Pre-assembled with Nut and EO-PSR Cutting Ring

CONNECTION 1 TYPE: Male 24° Cone

CONNECTION 2 SIZE: 8 mm (O.D.)

CONNECTION 2 TYPE: Male 24° Cone

CONNECTION 1 SIZE: 8 mm (O.D.)

PRODUCT OVERVIEW

Parker ball bearing rotary fittings are used to connect a fixed point to a rotating, swinging or moving part via hoses. These products are used to prevent torsion and small hose radius.

The ball bearing rotary fittings are suitable for hydraulic oils and lubricants on mineral oil base as flow media.

The construction of this service-proved product range is characterized by a compact, maintenance-free construction. The ball bearing rotary fittings have a combined ball and plain bearing with constant lubrication, a low starting torque and wear-resistant annular piston sealings.

Markets:

- Chemical Industries
- Plant engineering
- Power stations
- Cable storage

Applications:

- Suitable for general hydraulic applications.

Features/ Benefits of the ball bearing rotary fittings:

- Parker ball bearing rotary fittings help to avoid torsion of hoses and therefore improve the life cycle of these products
- Parker ball bearing rotary fittings have a high corrosion resistant surface.
- The construction of the ball bearing fittings is maintenance-free, so that the costs for maintenance will be reduced.

Technical specifications:

Materials: Casing, body nut of steel. Annular piston sealing: POM/FKM. Eolastic sealing: NBR, also available in FKM.

Nominal temperatures: -40 °C up to +95 °C

Construction Systems:

8 different versions with one rotational axis. Multiaxial rotary couplings on request. Tube connections according to DIN 2353, series S. Maximum working pressure 350 bar (peak pressure)

Male stud sealing by Eolastic seals of NBR

Male stud with metric parallel or BSPP thread.

TECH SPECIFICATIONS

CONNECTION 2 TYPE	Male
INDUSTRY	Automotive
FOR FLUID TYPE	Fuels
INDUSTRY	Transportation
FOR FLUID TYPE	Hydraulic Fluids
INDUSTRY	Marine
PRODUCT SERIES	EO Heavy
INDUSTRY	Construction
FOR FLUID TYPE	Chemicals
INDUSTRY	Industrial Manufacturing Equipment
FOR FLUID TYPE	Steam
INDUSTRY	Agriculture
FOR FLUID TYPE	Gases
INDUSTRY	Material Handling
SEAL TYPE	Sealing Edge
CONNECTION 2 TYPE	24° Cone
CONNECTION 1 TYPE	24° Cone
APPLICATION	Oilfield
DIVISION	High Pressure Connectors Europe Division
SPECIFICATIONS MET	ISO 8434
CONFIGURATION	Tube to Tube
MAXIMUM AMBIENT TEMPERATURE	300 °C
CONNECTION 2 SIZE	8 mm Tube O.D.
BODY MATERIAL	Steel
DIVISION	High Pressure Connectors Europe Division
CONNECTION 1 TYPE	Male

APPLICATION	Packaging
MAXIMUM FLUID TEMPERATURE	300 °C
PRODUCT STYLE	Rotary
BRAND	Ermeto
MAXIMUM AMBIENT TEMPERATURE	572 °F
CONNECTION 1 SIZE	8 mm Tube O.D.
MAXIMUM FLUID TEMPERATURE	572 °F
MINIMUM AMBIENT TEMPERATURE	-40 °C
APPLICATION	Fuel Transfer
MINIMUM FLUID TEMPERATURE	-40 °F
SHAPE	Straight
APPLICATION	Hydraulics
PRODUCT TYPE	Hydraulic DIN Fittings
ACCESSORIES INCLUDED	Pre-assembled with Nut and EO-PSR Cutting Ring
MINIMUM AMBIENT TEMPERATURE	-40 °F
APPLICATION	Chemical Transfer
MINIMUM FLUID TEMPERATURE	-40 °C
MAXIMUM OPERATING PRESSURE	420 bar
APPLICATION	Mobile Equipment
TECHNOLOGY	Fluid & Gas Handling
SEAL MATERIAL	n/a
NOMINAL INSIDE DIAMETER	DN 5