

Product datasheet

Specifications



Lexium 62 Single Drive - 6 A - accessory kit included

LXM62DU60C21000

EAN Code: 3606485317779

Main

Range of product	PacDrive 3
Device short name	LXM 62
Product or component type	Single drive
Component name	LXM62

Complementary

Product compatibility	Servo motor SHS Servo motor SH3 (55 mm, 1 motor stacks)optimized in terms of torque and speed Servo motor SH3 (55 mm, 2 motor stacks)optimized in terms of torque and speed Servo motor SH3 (55 mm, 3 motor stacks)optimized in terms of torque and speed Servo motor SH3 (70 mm, 1 motor stacks)optimized in terms of torque and speed Servo motor SH3 (70 mm, 2 motor stacks)optimized in terms of high torque Servo motor SH3 (70 mm, 3 motor stacks)optimized in terms of high torque Servo motor SH3 (100 mm, 1 motor stacks)optimized in terms of high torque Servo motor MH3 (70 mm, 1 motor stacks)optimized in terms of torque and speed
Network number of phases	Three phase
[Us] rated supply voltage	400 V (- 10...10 %) for three phase 230 V (- 10...10 %) for three phase 230 V (- 10...10 %) for single phase
Supply frequency	50/60 Hz - 5...5 %
Continuous output current	2 A at 4 kHz
Output current 3s peak	6 A at 4 kHz
Continuous power	0.95 kW
Nominal power	0.95 kW
Switching frequency	8 kHz
Overvoltage category	III
Electrical connection	Terminal, clamping capacity: 0.2...15 mm², AWG 24...AWG 16 (CN4) Terminal, clamping capacity: 0.5...16 mm², AWG 20...AWG 6 (CN5) Terminal, clamping capacity: 0.75...16 mm², AWG 18...AWG 6 (CN6) Terminal, clamping capacity: 0.2...6 mm², AWG 24...AWG 10 (CN7)
Tightening torque	CN1: 2.5 N.m
Number of inputs	2 digital 2 touch probe
Discrete input voltage	24 V DC for - 20...25 %
Number of outputs	2 digital
Discrete output voltage	24 V DC
Safety function	STO (safe torque off)
Communication interface	SERCOS III, integrated

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Depth	270 mm
Height	310 mm
Width	44.5 mm
Net weight	3 kg

Environment

Standards	CSA C22.2 No 14 ISO 13849-2 UL 508C IEC 62061 IEC 61800-5-2 ISO 13849-1 IEC 61800-3 IEC 61508 IEC 61800-5-1
Product certifications	CE TÜV UL CSA EAC
IP degree of protection	IP20 conforming to IEC 60529
Vibration resistance	10 m/s² conforming to IEC 60721-3-3
Shock resistance	100 m/s² conforming to IEC 60721-3-3
Pollution degree	2 conforming to IEC 61800-5-2
Environmental characteristic	3K3 conforming to IEC 60721-3-3
Relative humidity	5...85 %
Ambient air temperature for operation	5...55 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.000 cm
Package 1 Width	33.000 cm
Package 1 Length	44.000 cm
Package 1 Weight	3.840 kg
Unit Type of Package 2	S06
Number of Units in Package 2	10
Package 2 Height	75.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	46.500 kg

Logistical informations

Country of origin	FR
-------------------	----

Contractual warranty

Warranty	18 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	60beca05-ce1c-43ef-b5f4-b7c0f3eb7d27
REACH Regulation	REACH Declaration
PVC free	Yes

Use Again

Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No