

Note: This datasheet may be out of date

Please download the latest datasheet of CSTCE10M0G52A-R0 from the official website of Murata

Manufacturing Co., Ltd.

https://www.murata.com/en-us/products/productdetail?partno=CSTCE10M0G52A-R0

CSTCE10M0G52A-R0










Appearance & Shape







MURATA's package technology expertise has enabled the development of the Chip CERALOCK(R) with built-in load capacitors.

This diverse series owes its development to MURATA's original mass production techniques and high reliability, and has achieved importance in the worldwide automotive market.

Features

- 1. High reliability and available for a wide temperature range.
- 2. Oscillation circuits do not require external load capacitors.
- 3. Available for a wide frequency range.
- 4. Extremely small and have a low profile.
- 5. No adjustment is necessary for oscillation circuits.



Automotive Usage	Powertrain/Safety
Other Usage	Automotive



Packaging Information

Packaging	Specifications	Minimum Order Quantity
R0	180mm Embossed Tape	3000

1 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2019/06/12

Note: This datasheet may be out of date. $\underline{ \text{Please download the latest datasheet of CSTCE10M0G52A-R0 from the official website of Murata} \\$

Manufacturing Co., Ltd. https://www.murata.com/en-us/products/productdetail?partno=CSTCE10M0G52A-R0

CSTCE10M0G52A-R0



Product Type	Ceramic Resonator (CERALOCK®)
Series	CSTCE_G_A
Frequency	10.0MHz
Frequency Tolerance	+/-0.50% max.
Operating Temperature Range	-40°C to 125°C
Frequency Shift by Temperature	+/-0.20% max.
Frequency Aging	+/-0.10% max.
Resonant Impedance (R1)	40ohm max.
Built-in Load Capacitance(CL1/CL2)	10pF
Shape	SMD
Wash	available
L x W (size)	3.2x1.3mm

2 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/