

AMP | AMP M Series

TE Internal #: 213300-2

Housing, Plug, Crimp, Cable-to-Cable, UL 94V-0, 34 Position, 3.81 mm [.15 in] Centerline, AMP M Series, Rectangular Wire & Cable

Connectors & Housings

View on TE.com >



Connectors > Rectangular Connectors > Standard Rectangular Connectors











Connector Product Type: Housing
Connector & Housing Type: Plug

Termination Method to Wire & Cable: Crimp

Connector System: Cable-to-Cable

Contact Retention Within Housing: With

Features

Product Type Features

Assambly Paguirament	Unassembled Kit
Assembly Requirement	Unassembled Kit
Connector Product Type	Housing
Connector & Housing Type	Plug
Connector System	Cable-to-Cable
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Number of Signal Positions	34
Number of Power Positions	4
Number of Positions	34
Number of Rows	4
Electrical Characteristics	

250 VAC

Operating Voltage



Primary Product Color	Black
Contact Features	
Contact Type	Pin
Contact Retention Within Housing	With
Contact Current Rating (Max)	14 A
Termination Features	
Termination Method to Wire & Cable	Crimp
Mechanical Attachment	
Strain Relief	With
Panel Mount Feature	Without
Contact Retention Type Within Housing	Locking Spring
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Material	Phenolic GF
Centerline (Pitch)	3.81 mm[.15 in]
Dimensions	
Dimensions Row-to-Row Spacing	4.57 mm[.18 in]
	4.57 mm[.18 in] 21.03 mm[.828 in]
Row-to-Row Spacing	
Row-to-Row Spacing Connector Width	21.03 mm[.828 in]
Row-to-Row Spacing Connector Width Wire Size	21.03 mm[.828 in] 30 – 14 AWG
Row-to-Row Spacing Connector Width Wire Size Connector Length	21.03 mm[.828 in] 30 – 14 AWG
Row-to-Row Spacing Connector Width Wire Size Connector Length Usage Conditions	21.03 mm[.828 in] 30 – 14 AWG 52.07 mm[2.05 in]
Row-to-Row Spacing Connector Width Wire Size Connector Length Usage Conditions Operating Temperature Range	21.03 mm[.828 in] 30 – 14 AWG 52.07 mm[2.05 in]
Row-to-Row Spacing Connector Width Wire Size Connector Length Usage Conditions Operating Temperature Range Operation/Application	21.03 mm[.828 in] 30 – 14 AWG 52.07 mm[2.05 in] -55 – 150 °C[-67 – 302 °F]
Row-to-Row Spacing Connector Width Wire Size Connector Length Usage Conditions Operating Temperature Range Operation/Application Circuit Application	21.03 mm[.828 in] 30 – 14 AWG 52.07 mm[2.05 in] -55 – 150 °C[-67 – 302 °F]
Row-to-Row Spacing Connector Width Wire Size Connector Length Usage Conditions Operating Temperature Range Operation/Application Circuit Application Industry Standards	21.03 mm[.828 in] 30 – 14 AWG 52.07 mm[2.05 in] -55 – 150 °C[-67 – 302 °F] Power & Signal
Row-to-Row Spacing Connector Width Wire Size Connector Length Usage Conditions Operating Temperature Range Operation/Application Circuit Application Industry Standards Glow Wire Rating	21.03 mm[.828 in] 30 – 14 AWG 52.07 mm[2.05 in] -55 – 150 °C[-67 – 302 °F] Power & Signal Standard Part - Not Glow Wire
Row-to-Row Spacing Connector Width Wire Size Connector Length Usage Conditions Operating Temperature Range Operation/Application Circuit Application Industry Standards Glow Wire Rating UL Flammability Rating	21.03 mm[.828 in] 30 – 14 AWG 52.07 mm[2.05 in] -55 – 150 °C[-67 – 302 °F] Power & Signal Standard Part - Not Glow Wire



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts



Also in the Series | AMP M Series





Board-to-Board Jumpers & Shunts(5)




Connector Caps & Covers(14)



Connector Hardware(46)



Connector Strain Relief(13)



PCB Headers & Receptacles(9)



Rack & Panel Connectors(1)



Rectangular Power Connectors(82)



Wire-to-Board Headers & Receptacles (1)

Customers Also Bought



TE Part #YDIV44E25-35PNC009
RECP ASSY



TE Part #213522-1 M-SERIES KIT 34P V.35



TE Part #YDIV46E13-35PNC003
PLUG ASSY



TE Part #YDIV46E13-35SNC003
PLUG ASSY



TE Part #1-66108-5
III+ SKT,26-24,TIN,STRIP



TE Part #2313228-2 NanoRF BACKPLANE MODULE, 12 PSN, AL




TE Part #1897702-2 JPT 2P PLUG ASS'Y



TE Part #YDTS32W21RV0010000

DUST COVER ASSEM





Documents



Product Drawings

34 PASSM KIT,M SER (CC,JS)

English

CAD Files

Customer View Model

ENG_CVM_CVM_213300-2_L.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_213300-2_L.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_213300-2_L.3d_igs.zip

English

3D PDF

3D

3D PDF

English

Customer View Model

ENG_CVM_213300-2_H.2d_dxf.zip

English

Customer View Model

ENG_CVM_213300-2_H.3d_igs.zip

English

Customer View Model

ENG_CVM_213300-2_H.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

M_SERIES_PIN_AND_SOCKET_CONNECTORS

English